LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH50M 144157-1216 - Rear Differential

Sample No: LH0255452

Sodium

Oil Type: LIEBHERR SYNTOGEAR PLUS 75W-90

2

ppm

5							
U Sam	ple Info	rmation					
Sample Number		LH0255452	LH0255440	LH0225085			
Sample Date		21 Jun 2024	17 Nov 2023	15 Feb 2023			
Machine Hours		3338	2077	472			
Oil Hours		0	0	0			
Oil Changed		N/A	N/A	Changed			
Sample Status		NORMAL	NORMAL	NORMAL			
Oil Condition							
Visc @ 40°C	cSt	108	O 110	O 144			
-4							
Con	taminati	on					
Water	%	NEG	NEG	NEG			
Silicon	ppm	7	O 7	1 3			

	le le	U –	0 -	_	
Potassium	ppm	○ <1	3	O 2	
(O) Was	ır Metals				
Iron	ppm	27	O 21	O 15	
Copper	ppm	56	47	0 8	
Lead	ppm	1	2	O <1	
Tin	ppm	0	O 0	O 0	
Aluminum	ppm	 <1	<1	O <1	
Chromium	ppm	 <1	O 0	O <1	
Molybdenum	ppm	2	O 2	0 8	
Nickel	ppm	 <1	O <1	O 0	
Titanium	ppm	0	0	0	
Silver	ppm	<1	<1	0	
Manganese	ppm	○ <1	O <1	O <1	
Vanadium	ppm	0	0	0	

02

• 41.144.111	PP	•			
Addi	# !				
	tives	0.01	0.00	000	
Calcium	ppm	91	90	306	
Magnesium	ppm	1	1	O 2	
Zinc	ppm	49	43	58	
Phosphorus	ppm	1276	O 1329	O 1619	
Barium	ppm	<1	O <1	O 2	
Boron	ppm	240	248	1 1	



CALGARY METALS (1985) LTD. 3415 OGDEN RD. SE.

CALGARY, AB

Contact: Steve Goodzeck sgoodzeck@calgarymetal.com

T: (403)262-4542

F:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:CAL341CALUnique No:5802215Signed:Wes DavisReport Date:02 Jul 2024

CONSTRUCTION EQUIPMENT





Graphs

