

LIEBHERR

CONSTRUCTION EQUIPMENT



LIEBHERR A934 038332-1006 - Rear Left Wheel Hub

Sample No: VCE104382

Oil Type: GEAR OIL SAE 80W90



SAMPLE INFORMATION

| | | | | |
|---------------|-------------|-------------|-------------|-------------|
| Sample Number | VCE104382 | DJJ007505 | DJJ008603 | LHMC040996 |
| Sample Date | 01 May 2019 | 23 Jan 2013 | 28 Mar 2012 | 28 Jul 2011 |
| Machine Hours | 13156 | 7377 | 6219 | 5209 |
| Oil Hours | 0 | 1000 | 2000 | 1000 |
| Oil Changed | Changed | Changed | Changed | Not Changd |
| Sample Status | NORMAL | NORMAL | NORMAL | NORMAL |

AMERICAN STATE EQUIPMENT CO.
 2400 NORTH 14TH AVENUE
 WAUSAU, WI
 US 54401
 Contact: CHRIS BARTNIK
 cbartnik@amstate.com
 T: (715)675-6900
 F: (715)675-9748



OIL CONDITION

| | | | | | |
|-------------|-----|-----|-------|-------|-------|
| Visc @ 40°C | cSt | 124 | 130.6 | 129.5 | 131.2 |
|-------------|-----|-----|-------|-------|-------|



CONTAMINATION

| | | | | | |
|-----------|-----|----|----|---|---|
| Silicon | ppm | <1 | 3 | 3 | 1 |
| Sodium | ppm | <1 | <1 | 3 | 4 |
| Potassium | ppm | 10 | <1 | 0 | 1 |



WEAR METALS

| | | | | | |
|------------|-----|----|----|----|----|
| Iron | ppm | 26 | 39 | 72 | 46 |
| Copper | ppm | 11 | 12 | 19 | 12 |
| Lead | ppm | <1 | <1 | 0 | 0 |
| Tin | ppm | 0 | 0 | 0 | 0 |
| Aluminum | ppm | <1 | 0 | 2 | <1 |
| Chromium | ppm | <1 | <1 | 1 | <1 |
| Molybdenum | ppm | 0 | <1 | <1 | <1 |
| Nickel | ppm | 1 | <1 | 0 | <1 |
| Titanium | ppm | 0 | 0 | 0 | 0 |
| Silver | ppm | 0 | 0 | 0 | 0 |
| Manganese | ppm | <1 | 1 | 2 | 1 |
| Vanadium | ppm | 0 | 0 | <1 | 0 |



ADDITIVES

| | | | | | |
|------------|-----|-----|-----|------|------|
| Calcium | ppm | 8 | 10 | 8 | 9 |
| Magnesium | ppm | <1 | <1 | 0 | 1 |
| Zinc | ppm | 8 | 18 | 26 | 25 |
| Phosphorus | ppm | 680 | 955 | 1010 | 1065 |
| Barium | ppm | 0 | 0 | 0 | 0 |
| Boron | ppm | 19 | 167 | 168 | 191 |

Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 80W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: LEC0008
 Unique No: 8618297
 Signed: Wes Davis
 Report Date: 05 Jun 2019



GRAPHS

