
## LIEBHERR

**CONSTRUCTION EQUIPMENT** 

### LIEBHERR R930 056356-1716 - Left Final Drive

Sample No: LH0258222

Oil Type: LIEBHERR GEAR BASIC 90 LS



oup.o otatao				
OILCO	<b>NDITION</b>			
Visc @ 40°C	cSt	<b>198</b>	 	

CONTAMINATION						
Silicon	ppm	<b>3</b>				
Sodium	ppm	<b>3</b>				
Potassium	ppm	<b>2</b>				

WEAR METALS					
Iron	ppm	<b>160</b>			
Copper	ppm	<b>0</b>			
Lead	ppm	<b>0</b>			
Tin	ppm	<b>0</b>			
Aluminum	ppm	<b>1</b>			
Chromium	ppm	<b>2</b>			
Molybdenum	ppm	<b>0</b>			
Nickel	ppm	<b>0</b>			
Titanium	ppm	0			
Silver	ppm	0			
Manganese	ppm	<b>2</b>			
Vanadium	ppm	0			

ADDITIVES						
Calcium	ppm	<b>21</b>				
Magnesium	ppm	<b>5</b>				
Zinc	ppm	<b>22</b>				
Phosphorus	ppm	<b>1087</b>				
Barium	ppm	<b>24</b>				
Boron	ppm	<b>1</b>				



ACECO 10119 RESIDENCY ROAD MANASSAS, VA US 20110 Contact: RON BROCK

T: (703)392-0111 F: (703)331-5604

#### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:ACEMANUnique No:10635928Signed:Don BaldridgeReport Date:10 Sep 2023

# CONSTRUCTION EQUIPMENT





#### **GRAPHS**

