LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH50M 1216-109503 - Swing Drive

Sample No: LHMC162817

Oil Type: GEAR OIL SAE 75W90

ā				
SAN	APLE INFO	DRMATION		
Sample Number		LHMC162817	LHMC163543	
Sample Date		15 Sep 2023	23 Mar 2023	
Machine Hours		6608	5400	
Oil Hours		0	0	
Oil Changed		Not Changd	Not Changd	
Sample Status		NORMAL	ATTENTION	
A				
OIL	CONDITIO	ON		
Visc @ 40°C	cSt	158	54.6	
CON	ITAMIN <i>A</i>	TION		
Silicon		22	O <1	
Sodium	ppm	0 8	0 2	
Potassium	ppm	0 4	0 <1	
	ppm	4	0 < 1	
◎ WE	AR META	LS		
Iron	ppm	835	○ 280	
Copper	ppm	216	O 68	
Lead	ppm	() <1	O 0	
Tin	ppm	13	O 3	
Aluminum	ppm	2	0	
Chromium	ppm	5	O 1	
Molybdenum	ppm	0	O <1	
Nickel	ppm	○ <1	O 0	
Titanium	ppm	0	0	
Silver	ppm	0	0	
Manganese	ppm	7	O 3	
Vanadium	ppm	0	0	
ADD	ITIVES			
Calcium	ppm	40	○ 36	
Magnesium	ppm	5	O 4	
Zinc	ppm	53	0 1	

922

120

0



AHLSTROM-MUNKSJO NA SPECIALTY

PO BOX 600 KAUKAUNA, WI US 54130

Contact: JOE SEITZ

joe.seiltz@ahlstrom-munksjo.com

T: F:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:AHLKAUUnique No:10660478Signed:Don BaldridgeReport Date:26 Sep 2023

2215

2

40

Phosphorus

Barium

Boron

ppm

ppm

ppm





GRAPHS

