# LIEBHERR





### [[GALENA ROAD GRAVEL]] LIEBHERR L556 068648-1827 - Trans

Sample No: LHMC124463

Oil Type: LIEBHERR GEAR MF 80W

5				
SAM	<b>PLE INFO</b>	<b>DRMATION</b>		
Sample Number		LHMC124463	 	
Sample Date		11 Sep 2023	 	
Machine Hours		1000	 	
Oil Hours		1000	 	
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
OILC	ONDITIO	ON		
Visc @ 40°C	cSt	42.5	 	
-4		-		
CON	TAMINA	TION		
	IAMINA			
Silicon	ppm	<b>9</b>	 	
Sodium	ppm	<b>18</b>	 	
Potassium	ppm	<b>4</b>	 	
◎ WEA				
WEA	R META	LS		
Iron	ppm	<b>14</b>	 	
Copper	ppm	<b>2</b>	 	
Lead	ppm	<b>0</b> <1	 	
Tin	ppm	<b>0</b>	 	
Aluminum	ppm	<b>0</b>	 	
Chromium	ppm	<b>0</b> <1	 	
Molybdenum	ppm	<b>0</b> <1	 	
Vickel	ppm	<1	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	<b>()</b> <1	 	
Vanadium	ppm	0	 	
ADDI	ITIVES			
Calcium	ppm	<b>3462</b>	 	



#### FINKBINER EQUIPMENT

3501 N. MAIN ST EAST PEORIA, IL US 61611

Contact: ZACH WAKID zwakid@finkbiner.com T: (309)863-4831

F:

#### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:FINEASILUnique No:10696460Signed:Sean FeltonReport Date:17 Oct 2023

**9** 

**2** 

**1468** 

**1180** 

**142** 

Magnesium

Phosphorus

Zinc

Barium

Boron

ppm

ppm

ppm

ppm

ppm

## LIEBHERR

CONSTRUCTION EQUIPMENT





#### **GRAPHS**

