## LIEBHERR





Sample No: LHMC129548

Oil Type: GEAR OIL ISO 320

=				
SAM	<b>PLE INFO</b>	RMATION		
Sample Number		LHMC129548	 	
Sample Date		10 Oct 2023	 	
Machine Hours		8874	 	
Oil Hours		0	 	
Oil Changed		N/A	 	
Sample Status		NORMAL	 	
Sample Status		NONWAL		
A		<b>.</b> .		
	ONDITIO	N		
Visc @ 40°C	cSt	<b>285</b>	 	
CONT	<b>TAMINA</b>	ION		
Silicon	ppm	<b>○</b> 11	 	
Sodium	ppm	O 2	 	
Potassium	ppm	<b>0</b>	 	
Ø WEA		_		
WEA	R METAL	5		
Iron	ppm	<b>67</b>	 	
Copper	ppm	<b>24</b>	 	
Lead	ppm	<b>0</b>	 	
Tin	ppm	<b>0</b>	 	
Aluminum	ppm	<b>0</b>	 	
Chromium	ppm	<b>0</b>	 	
Molybdenum	ppm	<b>0</b>	 	
Nickel	ppm	<b>0</b>	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	<b>0</b> <1	 	
Vanadium	ppm	0	 	
MII.				
ADDI	TIVES			
		0.140		
Calcium	ppm	<b>142</b>	 	
Magnesium	ppm	<b>0</b> 0	 	
Zinc	ppm	<b>42</b>	 	
Phosphorus	ppm	<b>355</b>	 	
Barium	ppm	<b>0</b> 0	 	
Boron	ppm	<b>26</b>	 	

LIEBHERR MINING EQUIPMENT CO

5800 S DOUGLAS HWY GILLETTE, WY

US 82718

Contact: DUSTIN HARDEN

DUSTIN.HARDEN@LIEBHERR.COM

T: (307)660-8763

F:

## Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is suitable for further service.

Depot:LIEGILUnique No:10726908Signed:Sean FeltonReport Date:07 Nov 2023

## LIEBHERR

CONSTRUCTION EQUIPMENT





## **GRAPHS**

