## LIEBHERR

### **CONSTRUCTION EQUIPMENT**



Sample No: LH0223476

Molybdenum

Nickel

Silver

Titanium

Manganese

Vanadium

ppm

ppm

ppm

ppm

ppm

ppm

<1

0

0

<1

**0** 

Oil Type: DURALENE Posi-Traction 80W90

_									
O SAN	APLE INFO	DRMATION							
Sample Number		LH0223476	LH0223465	LH0223454					
Sample Date		20 Oct 2023	23 Apr 2023	07 Jul 2022					
Machine Hours		3182	2000	1000					
Oil Hours		0	0	0					
Oil Changed		Not Changd	N/A	N/A					
Sample Status		NORMAL	NORMAL	NORMAL					
OIL	CONDITIO	ON							
Visc @ 40°C	cSt	<b>129</b>	O 126	<b>127</b>					
-4									
CONTAMINATION									
Silicon	ppm	<b>3</b>	O 2	<b>2</b>					
Sodium	ppm	<b>2</b>	O 2	O 0					
Potassium	ppm	<b>0</b>	O 0	O <1					
(O) WE	AR META	LS							
Iron	ppm	<b>○</b> 16	O 16	O 14					
Copper	ppm	O 29	O 23	O 9					
Lead	ppm	00	00	0 <1					
Tin	ppm	00	0 0	O <1					
Aluminum	ppm	<b>0</b> 0	0 <1	O <1					
Chromium	ppm	<b>0</b> 0	0 <1	0 <1					



# CONSERVIT INC. PO BOX 1517 HAGERSTOWN, MD US 21740 Contact: DON LONG

Contact: DON LONG dlong@conservit.biz T: (301)791-0100 F: (301)739-8548

#### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

ADDIT	TIVES				
Calcium	ppm	179	180	199	
Magnesium	ppm	25	28	26	
Zinc	ppm	121	110	113	
Phosphorus	ppm	1380	1318	1240	
Barium	ppm	41	37	31	
Boron	ppm	125	130	137	

2

 $\bigcirc$  0

2

Depot:CONHAGUnique No:10740338Signed:Don BaldridgeReport Date:15 Nov 2023

## LIEBHERR

CONSTRUCTION EQUIPMENT





#### **GRAPHS**

