

LIEBHERR

CONSTRUCTION EQUIPMENT



[[KIMMEL]] LIEBHERR LH50M 1216-117 615 - Rear Right Wheel

Sample No: LH0268508

Oil Type: LIEBHERR GEAR BASIC 90 LS



RECO EQUIPMENT INC
 10461 GRAND RIVER RD
 BRIGHTON, MI
 US 48116
 Contact: MATT VISEL
 MVISEL@RECOEQUIP.COM
 T: (810)299-1731
 F:



SAMPLE INFORMATION

Sample Number	LH0268508	LH0243177	LHMC122694	---
Sample Date	18 Dec 2023	14 Apr 2023	04 Dec 2020	---
Machine Hours	8068	6895	2028	---
Oil Hours	1173	1000	860	---
Oil Changed	Changed	Changed	Changed	---
Sample Status	NORMAL	NORMAL	NORMAL	---



OIL CONDITION

Visc @ 40°C	cSt	188	173	147	---
-------------	-----	-----	-----	-----	-----



CONTAMINATION

Water	%	NEG	NEG	NEG	---
Silicon	ppm	<1	<1	15	---
Sodium	ppm	4	<1	2	---
Potassium	ppm	<1	<1	2	---



WEAR METALS

Iron	ppm	15	14	244	---
Copper	ppm	8	5	54	---
Lead	ppm	0	0	<1	---
Tin	ppm	0	0	0	---
Aluminum	ppm	2	0	0	---
Chromium	ppm	<1	0	1	---
Molybdenum	ppm	0	0	<1	---
Nickel	ppm	0	<1	<1	---
Titanium	ppm	0	0	<1	---
Silver	ppm	0	0	<1	---
Manganese	ppm	0	<1	4	---
Vanadium	ppm	0	0	0	---



ADDITIVES

Calcium	ppm	17	29	208	---
Magnesium	ppm	2	<1	5	---
Zinc	ppm	10	29	117	---
Phosphorus	ppm	2809	2203	1907	---
Barium	ppm	0	0	5	---
Boron	ppm	0	0	6	---

Diagnosis


Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: RECBRILH
 Unique No: 10849969
 Signed: Don Baldrige
 Report Date: 31 Jan 2024




GRAPHS

Ferrous Alloys



Non-ferrous Metals



Viscosity @ 40°C

