LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH60 115240-1529 - Splitter Box

Sample No: LHMC107773

Oil Type: LIEBHERR GEAR BASIC 90 LS



Con	taminati	on				
Water	%	NEG	NEG	NEG	NEG	
Silicon	ppm	7	3	O 2	02	
Sodium	ppm	1	O 0	<1	O <1	
Potassium	ppm	0	O 1	O 2	O 0	

Wea	r Metals				
Iron	ppm	17	O 14	O 13	9
Copper	ppm	0 <1	O 2	1	 <1
Lead	ppm	0	O <1	O	0
Tin	ppm	0	0	O <1	0
Aluminum	ppm	0 <1	O 2	O <1	3
Chromium	ppm	0	O <1	O <1	0
Molybdenum	ppm	0	0	O <1	0
Nickel	ppm	0	0	O <1	0
Titanium	ppm	0	<1	0	0
Silver	ppm	0	0	0	0
Manganese	ppm	O <1	0	O <1	 <1
Vanadium	ppm	0	0	0	0

Vanadium ppm 0 0	0								
Additives									
Calcium ppm 49 ○ 104 ○ 83	99								
Magnesium ppm 0 0	3								
Zinc ppm ○ 48 ○ 82 ○ 91	○ 80								
Phosphorus ppm ○ 1845 1116 1054	523								
Barium	O 0								
Boron	0								



DAVIS INDUSTRIAL INC. 9920 RICHMOND HIGHWAY LORTON, VA US 22079 Contact: JAMIE

jamie.davisindustries@gmail.com

T: F:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:DAVLORVAUnique No:11002876Signed:Wes DavisReport Date:29 Apr 2024





Graphs

