# LIEBHERR





Sample No: LHMC129572

Oil Type: GEAR OIL ISO 320

_				
Sami	ple Infor	mation		
Sample Number		LHMC129572	 	
Sample Date		04 Apr 2024	 	
Machine Hours		7183	 	
Oil Hours		0	 	
Oil Changed		N/A	 	
Sample Status		NORMAL	 	
Oampie Otatus		HOHWAL		
OilCo	ondition			
Visc @ 40°C	cSt	<b>273</b>	 	
visc @ 40 C	USI	<u> </u>	 	
Cont	aminatio	on		
Water	%	NEG	 	
Silicon	ppm	<b>6</b>	 	
Sodium	ppm	<b>3</b>	 	
Potassium	ppm	<b>2</b>	 	
<b>**</b>				
<b>O</b> West	r Metals			
Iron	ppm	<b>50</b>	 	
Copper	ppm	<b>5</b>	 	
Lead 	ppm	<b>O</b> <1	 	
Tin	ppm	0	 	
Aluminum	ppm	0	 	
Chromium	ppm	0	 	
Molybdenum	ppm	0	 	
Nickel	ppm	0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	01	 	
Vanadium	ppm	0	 	
Addi	tives			
Calcium	ppm	<b>0</b> 0	 	
Magnesium	ppm	0	 	
Zinc	ppm	0	 	
Phosphorus	ppm	302	 	
Barium	ppm	0 0	 	
Danum	PPIII	0 0		

LIEBHERR MINING EQUIPMENT CO

5800 S DOUGLAS HWY GILLETTE, WY

US 82718

Contact: DUSTIN HARDEN

DUSTIN.HARDEN@LIEBHERR.COM

T: (307)660-8763

F:

#### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:LIEGILUnique No:11022351Signed:Wes DavisReport Date:13 May 2024

Contact/Location: DUSTIN HARDEN - LIEGIL

**8** 

ppm

Boron

## LIEBHERR

### **CONSTRUCTION EQUIPMENT**





### **Graphs**

