## LIEBHERR





Sample No: LHMC129569

Oil Type: GEAR OIL ISO 320

| Sami                  | ple Infor | mation                 |      |  |
|-----------------------|-----------|------------------------|------|--|
| Sample Number         |           | LHMC129569             | <br> |  |
| Sample Date           |           | 23 Apr 2024            | <br> |  |
| Machine Hours         |           | 7183                   | <br> |  |
| Oil Hours             |           | 0                      | <br> |  |
| Oil Changed           |           | N/A                    | <br> |  |
| Sample Status         |           | NORMAL                 | <br> |  |
| Varipic Otatus        |           | HOHWAL                 |      |  |
| OilCo                 | ondition  |                        |      |  |
| Visc @ 40°C           | cSt       | <b>259</b>             | <br> |  |
| VISC @ 40 C           | COL       | 239                    | <br> |  |
|                       |           |                        |      |  |
| Conto                 | aminatio  | on                     |      |  |
| Water                 | %         | NEG                    | <br> |  |
| Silicon               | ppm       | <b>10</b>              | <br> |  |
| Sodium                | ppm       | <b>0</b>               | <br> |  |
| Potassium             | ppm       | <b>2</b>               | <br> |  |
| ***                   |           |                        |      |  |
| <b>Weg</b>            | r Metals  | •                      |      |  |
|                       |           |                        |      |  |
| Iron                  | ppm       | <b>○</b> 70            | <br> |  |
| Copper                | ppm       | <b>0</b> 7             | <br> |  |
| Lead                  | ppm       | O <1                   | <br> |  |
| Tin                   | ppm       | O <1                   | <br> |  |
| Aluminum              | ppm       | <b>3</b>               | <br> |  |
| Chromium              | ppm       | 0 <1                   | <br> |  |
| Molybdenum<br>Nickel  | ppm       | O <1                   | <br> |  |
|                       | ppm       | O <1                   | <br> |  |
| Titanium              | ppm       | <1                     | <br> |  |
| Silver                | ppm       | <1                     |      |  |
| Manganese<br>Vanadium | ppm       | <b>2</b>               | <br> |  |
|                       | ppm       | <1                     | <br> |  |
| Addi                  | tives     |                        |      |  |
| Calcium               | ppm       | <b>0</b> 4             | <br> |  |
| Magnesium             | ppm       | ○ <1                   | <br> |  |
| Zinc                  | ppm       | <ul><li>○ 16</li></ul> | <br> |  |
| Phosphorus            | ppm       | <b>○</b> 340           | <br> |  |
| Barium                | ppm       | ○ 1                    | <br> |  |
| Darram                | ppiii     | 0.10                   |      |  |

LIEBHERR MINING EQUIPMENT CO

5800 S DOUGLAS HWY GILLETTE, WY

US 82718

Contact: DUSTIN HARDEN

DUSTIN.HARDEN@LIEBHERR.COM

T: (307)660-8763

F:

## Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:LIEGILUnique No:11097136Signed:Wes DavisReport Date:25 Jun 2024

**12** 

ppm

Boron

## LIEBHERR

**CONSTRUCTION EQUIPMENT** 





## **Graphs**

