CONSTRUCTION EQUIPMENT



LIEBHERR TT&E R954C 24925 (S/N 976-24925) - Left Final Drive

Sample No: LH0268749

Oil Type: LIEBHERR GEAR BASIC 90 LS

Sample Information					
Sample Number	1	LH0268749			
Sample Date		01 Jul 2024			
Machine Hours		11252			
Oil Hours		1500			
Oil Changed		Changed			
Sample Status		SEVERE			
Oil Co	ndition				
Visc @ 40°C	cSt	253			
-4					
Court	amination				
Conto	amination				
Water	%	0.269			
Silicon	ppm	1056			
Sodium	ppm	31			
Potassium	ppm	72			
	r Metals	2 0000			
Iron	ppm	2693			
Copper	ppm	0 424			
Lead	ppm	5			
Tin	ppm	O 39			
Aluminum	ppm	0 311			
Chromium	ppm	24			
Molybdenum	ppm	3			
Nickel	ppm	<u> </u>			
Titanium	ppm	16			
Silver	ppm	0			
Manganese	ppm	24			
Vanadium	ppm	<1			
Addi	tives				
Calcium	ppm	163			
Magnesium	ppm	29			
Zinc	ppm	128			
Phosphorus	ppm	2242			
Barium	ppm	0			
Boron	ppm	0 4			
Doron	PPIII	-			

LIEBHERR EQUIPMENT SOURCE

8200 FAYETTEVILLE ROAD RALEIGH, NC US 27603

Contact: SHERWOOD LUCAS sherwood.lucas@liebherr.com

T:

F: (919)329-0084

Diagnosis

We advise that you check all areas where dirt can enter the system. The oil change at the time of sampling has been noted. We advise that you inspect for the source(s) of wear. We recommend an early resample to monitor this condition. Bearing and/or bushing wear is indicated. Gear wear is indicated. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. There is a light concentration of water present in the oil. The oil is no longer serviceable due to the presence of contaminants.

Depot:LIEBHERRNCUnique No:11114097Signed:Sean FeltonReport Date:10 Jul 2024

Submitted By: SHERWOOD LUCAS

CONSTRUCTION EQUIPMENT





Graphs





