LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH50M 146105-1216 - Diesel Engine

Sample No: LH0284906

Oil Type: DIESEL ENGINE OIL SAE 30



ÉTATI	D'HUILE			
Visc 100°C	cSt	12.5	11.8	
Oxydation (PA)	%	87	211	

CONTAMINATION					
Eau	%	NEG	NEG		
% de suie	%	0	0		
Nitration (PA)	%	74	105		
Sulfatation (PA)	%	63	113		
Glycol	%	NEG	NEG		
Essence	%	<1.0	O 1.2		
Silicium	ppm	8	9		
Sodium	ppm	2	3		
Potassium	ppm	() <1	3		

10				
MéT	AUX D'U	ISURE		
Fer	ppm	6	O 11	
Cuivre	ppm	134	O 238	
Plomb	ppm	5	0 8	
Étain	ppm	() <1	O 1	
Aluminium	ppm	2	4	
Chrome	ppm	() <1	O <1	
Molybdène	ppm	56	45	
Nickel	ppm	0	O 0	
Titane	ppm	0	<1	
Argent	ppm	0	O 0	
Manganèse	ppm	0	1	
Vanadium	ppm	0	0	

ADDITIFS					
Calcium	ppm	1100	O 1343		
Magnésium	ppm	929	O 932		
Zinc	ppm	1103	O 841		
Phosphore	ppm	921	O 716		
Baryum	ppm	5	○ 32		
Bore	ppm	11	○ 82		



JOSEPH & COMPANY INC 257 VICTORIA ST N KITCHENER, ON CA N2H 5C9 Contact: Service Manager

T: F:

Diagnostic

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DIESEL ENGINE OIL SAE 30. Please confirm.All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

 Depot:
 JOS257KIT

 Unique No:
 5723690

 Signed:
 Kevin Marson

 Report Date:
 12 Feb 2024

LIEBHERR







GRAPHS

