

LIEBHERR

CONSTRUCTION EQUIPMENT



LIEBHERR L586 055418-1334 - Diesel Engine

Sample No: LH0276259

Oil Type: SAE 5W30



Information sur l'échantillon

Numéro d'échant.	LH0276259	LH0285114	LH0281406	LH0278962
Date d'échant.	14 May 2024	11 Feb 2024	21 Jan 2024	05 Nov 2023
Heures de la Machine	14463	13516	13061	12685
Heures de l'huile	0	0	0	0
Huile changée	Changed	Changed	Changed	N/A
Statut de l'échant.	NORMAL	NORMAL	NORMAL	NORMAL

CGC INC
 55 THIRD LINE RD
 HAGERSVILLE, ON
 CA N0A 1H0
 Contact: Mike Otterman
 motterman@cgcinco.com
 T: (905)768-2038
 F:



État d'huile

Visc 100°C	cSt	13.2	12.0	14.2	13.7
Oxydation (PA)	%	77	71	65	66



Contamination

Eau	%	NEG	NEG	NEG	NEG
% de suie	%	0	0	0	0
Nitration (PA)	%	73	68	59	60
Sulfatation (PA)	%	58	55	54	54
Glycol	%	NEG	NEG	NEG	NEG
Essence	%	<1.0	<1.0	<1.0	<1.0
Silicium	ppm	4	5	6	7
Sodium	ppm	4	5	4	3
Potassium	ppm	<1	<1	1	0

Diagnostic

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. Viscosity of sample indicates oil is within SAE 40 range, advise investigate. The condition of the oil is acceptable for the time in service.



Métaux d'usure

Fer	ppm	4	2	3	3
Cuivre	ppm	2	2	2	1
Plomb	ppm	<1	<1	<1	<1
Étain	ppm	0	0	0	0
Aluminium	ppm	1	2	2	2
Chrome	ppm	0	0	0	<1
Molybdène	ppm	57	59	57	57
Nickel	ppm	0	0	0	0
Titane	ppm	0	0	0	0
Argent	ppm	0	0	0	<1
Manganèse	ppm	0	0	0	0
Vanadium	ppm	0	0	0	0



Additifs

Calcium	ppm	1149	895	1067	1146
Magnésium	ppm	937	1068	950	911
Zinc	ppm	1161	1186	1151	1172
Phosphore	ppm	944	1029	981	950
Baryum	ppm	0	0	0	<1
Bore	ppm	8	28	1	3

Depot: CGCHAG
Unique No: 5776738
Signed: Kevin Marson
Report Date: 15 May 2024



Graphs

