# LIEBHERR

**CONSTRUCTION EQUIPMENT** 

## LIEBHERR 151293-1216 - Swing Drive

Sample No: LH0290905

Oil Type: GEAR OIL SAE 80W90



Contamination						
Eau	%	NEG				
Silicium	ppm	<b>6</b>				
Sodium	ppm	<b>4</b>				
Potassium	ppm	<b>2</b>				
Métaux d'usure						

77101	uon u os			
Fer	ppm	<b>375</b>	 	
Cuivre	ppm	<b>127</b>	 	
Plomb	ppm	<b>3</b>	 	
Étain	ppm	<b>14</b>	 	
Aluminium	ppm	<b>2</b>	 	
Chrome	ppm	<b>2</b>	 	
Molybdène	ppm	<b>0</b>	 	
Nickel	ppm	<b>○</b> <1	 	
Titane	ppm	0	 	
Argent	ppm	0	 	
Manganèse	ppm	<b>4</b>	 	
Vanadium	ppm	0	 	

Additifs							
Calcium	ppm	<b>22</b>					
Magnésium	ppm	<b>2</b>					
Zinc	ppm	<b>33</b>					
Phosphore	ppm	<b>2172</b>					
Baryum	ppm	<b>9</b>					
Bore	ppm	<b>26</b>					





1625066 ONTARIO LTD. 870 MACKAY RD PICKERING, ON CA L1W 2Y4

Contact: Service Manager

T: F:

#### Diagnostic

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 80W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

 Depot:
 162PIC

 Unique No:
 5786149

 Signed:
 Wes Davis

 Report Date:
 22 May 2024





### **Graphs**

