

# LIEBHERR

## CONSTRUCTION EQUIPMENT



### LIEBHERR LH22M 137772-1525 - Swing Drive

Sample No: LH0232639

Oil Type: GEAR OIL SAE 80W90



#### Information sur l'échantillon

Numéro d'échant.	LH0232639	---	---	---
Date d'échant.	28 May 2024	---	---	---
Heures de la Machine	2312	---	---	---
Heures de l'huile	0	---	---	---
Huile changée	Not Changed	---	---	---
Statut de l'échant.	NORMAL	---	---	---

**Excavation Dolbeau Inc.**  
493 - 2ieme Avenue  
Dolbeau-Mistassini, QC  
CA G8L 1V3  
Contact: Service Manager



#### État d'huile

Visc 40°C	cSt	● 168	---	---	---
-----------	-----	-------	-----	-----	-----

T:  
F:



#### Contamination

Eau	%	NEG	---	---	---
Silicium	ppm	● <1	---	---	---
Sodium	ppm	● 7	---	---	---
Potassium	ppm	● 2	---	---	---

#### Diagnostic

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 80W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.



#### Métaux d'usure

Fer	ppm	● 244	---	---	---
Cuivre	ppm	● 20	---	---	---
Plomb	ppm	● <1	---	---	---
Étain	ppm	● 5	---	---	---
Aluminium	ppm	● <1	---	---	---
Chrome	ppm	● 2	---	---	---
Molybdène	ppm	● 0	---	---	---
Nickel	ppm	● 0	---	---	---
Titane	ppm	● 0	---	---	---
Argent	ppm	● 0	---	---	---
Manganèse	ppm	● 3	---	---	---
Vanadium	ppm	● 0	---	---	---



#### Additifs

Calcium	ppm	● 18	---	---	---
Magnésium	ppm	● <1	---	---	---
Zinc	ppm	● 32	---	---	---
Phosphore	ppm	● 1898	---	---	---
Baryum	ppm	● 6	---	---	---
Bore	ppm	● 4	---	---	---

**Depot:** EXCDOL  
**Unique No:** 5788622  
**Signed:** Wes Davis  
**Report Date:** 03 Jun 2024



### Graphs

