

LIEBHERR

CONSTRUCTION EQUIPMENT



LIEBHERR L546 054052-1560 - Rear Differential

Sample No: LH0169001

Oil Type: GEAR OIL SAE 75W90



Information sur l'échantillon

Número d'échant.	LH0169001	LH0169014	LH0168988	LH0168975
Date d'échant.	11 Jun 2024	15 Jul 2022	14 Jun 2021	08 Dec 2020
Heures de la Machine	7137	3877	2095	1079
Heures de l'huile	0	0	0	0
Huile changée	Changed	Changed	Changed	Changed
Statut de l'échant.	NORMAL	NORMAL	NORMAL	NORMAL

MOOREFIELD EXCAVATING LTD.
 6297 WELLINGTON RD. 109S, RR #3
 HARRISTON, ON
 CA N0G 1Z0
 Contact: John Landman
 info@moorefieldex.ca
 T: (519)343-3571
 F: (519)510-3277



État d'huile

Visc 40°C	cSt	99.1	86.6	102	183



Contamination

Eau	%	NEG	NEG	NEG	NEG
Silicium	ppm	1	1	6	18
Sodium	ppm	6	2	4	11
Potassium	ppm	7	<1	1	4

Diagnostic

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.



Métaux d'usure

Fer	ppm	242	25	36	136
Cuivre	ppm	<1	0	<1	<1
Plomb	ppm	0	<1	<1	<1
Étain	ppm	0	0	0	0
Aluminium	ppm	<1	<1	<1	<1
Chrome	ppm	<1	0	<1	1
Molybdène	ppm	<1	0	<1	<1
Nickel	ppm	<1	<1	<1	<1
Titane	ppm	0	0	0	0
Argent	ppm	0	0	<1	<1
Manganèse	ppm	2	<1	<1	2
Vanadium	ppm	0	0	0	0



Additifs

Calcium	ppm	22	10	17	18
Magnésium	ppm	8	2	<1	1
Zinc	ppm	41	17	15	14
Phosphore	ppm	1740	3378	2269	2221
Baryum	ppm	<1	0	<1	<1
Bore	ppm	4	176	8	2

Depot: MOOPAL
 Unique No: 5812311
 Signed: Wes Davis
 Report Date: 09 Jul 2024



Graphs

