


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
Scoop 6 Yard
Machine Id
LHD6105
Component
Diesel Engine
Fluid
PETRO CANADA DURON HP 15W40 (18 LTR)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history 1	history 2
Sample Number	Client Info			PC0050466	---	---
Sample Date	Client Info			23 Apr 2023	---	---
Machine Age	hrs	Client Info		1130	---	---
Oil Age	hrs	Client Info		0	---	---
Oil Changed	Client Info			N/A	---	---
Sample Status				NORMAL	---	---

CONTAMINATION		method	limit/base	current	history 1	history 2
Fuel	WC Method	>5		<1.0	---	---
Glycol	WC Method			NEG	---	---

WEAR METALS		method	limit/base	current	history 1	history 2
Iron	ppm	ASTM D5185(m)	>100	69	---	---
Chromium	ppm	ASTM D5185(m)	>20	2	---	---
Nickel	ppm	ASTM D5185(m)	>4	0	---	---
Titanium	ppm	ASTM D5185(m)		<1	---	---
Silver	ppm	ASTM D5185(m)	>3	<1	---	---
Aluminum	ppm	ASTM D5185(m)	>20	4	---	---
Lead	ppm	ASTM D5185(m)	>40	<1	---	---
Copper	ppm	ASTM D5185(m)	>330	20	---	---
Tin	ppm	ASTM D5185(m)	>15	<1	---	---
Antimony	ppm	ASTM D5185(m)		0	---	---
Vanadium	ppm	ASTM D5185(m)		0	---	---
Beryllium	ppm	ASTM D5185(m)		0	---	---
Cadmium	ppm	ASTM D5185(m)		0	---	---


ADDITIVES		method	limit/base	current	history 1	history 2
Boron	ppm	ASTM D5185(m)	0	6	---	---
Barium	ppm	ASTM D5185(m)	0	0	---	---
Molybdenum	ppm	ASTM D5185(m)	60	60	---	---
Manganese	ppm	ASTM D5185(m)	0	1	---	---
Magnesium	ppm	ASTM D5185(m)	1010	994	---	---
Calcium	ppm	ASTM D5185(m)	1070	1379	---	---
Phosphorus	ppm	ASTM D5185(m)	1150	1114	---	---
Zinc	ppm	ASTM D5185(m)	1270	1307	---	---
Sulfur	ppm	ASTM D5185(m)	2060	2402	---	---
Lithium	ppm	ASTM D5185(m)		<1	---	---

CONTAMINANTS		method	limit/base	current	history 1	history 2
Silicon	ppm	ASTM D5185(m)	>25	9	---	---
Sodium	ppm	ASTM D5185(m)		4	---	---
Potassium	ppm	ASTM D5185(m)	>20	1	---	---


INFRA-RED		method	limit/base	current	history 1	history 2
Soot %	%	ASTM D7844*	>3	0.8	---	---
Nitration	Abs/cm	ASTM D7624*	>20	11.7	---	---
Sulfation	Abs/.1mm	ASTM D7415*	>30	24.6	---	---

FLUID DEGRADATION		method	limit/base	current	history 1	history 2
Oxidation	Abs/.1mm	ASTM D7414*	>25	20.9	---	---

OIL ANALYSIS REPORT











VISUAL		method	limit/base	current	history 1	history 2
Emulsified Water	scalar	Visual*	>0.2	NEG	---	---
Free Water	scalar	Visual*		NEG	---	---



FLUID PROPERTIES		method	limit/base	current	history 1	history 2
Visc @ 40°C	cSt	ASTM D7279(m)	118.2	114	---	---
Visc @ 100°C	cSt	ASTM D7279(m)	15.6	15.0	---	---
Viscosity Index (VI)	Scale	ASTM D2270*	139	136	---	---

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PC0050466 **Received** : 04 Jul 2023
Lab Number : **02567707** **Diagnosed** : 04 Jul 2023
Unique Number : 5604753 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: KV40, VI)

Lakeshore Gold Timmins West
 Timmins, ON
 CA
 Contact: Adam Koscielak
 adam.koscielak@HFSinclair.com
 T:
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.