


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
1416

Component
Rear Transmission (Auto)

Fluid
PETRO CANADA DuraDrive HD Synthetic 668 (30 LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history 1	history 2
Sample Number	Client Info			PC0061457	PC417059	---
Sample Date	Client Info			17 Apr 2023	08 Jun 2022	---
Machine Age	kms	Client Info		555407	500735	---
Oil Age	kms	Client Info		54672	44600	---
Oil Changed	Client Info			Changed	Changed	---
Sample Status				NORMAL	ABNORMAL	---





WEAR METALS		method	limit/base	current	history 1	history 2
PQ		ASTM D8184*	>105	0	---	---
Iron	ppm	ASTM D5185(m)	>230	68	61	---
Chromium	ppm	ASTM D5185(m)	>2	<1	0	---
Nickel	ppm	ASTM D5185(m)	>5	0	<1	---
Titanium	ppm	ASTM D5185(m)	>2	0	0	---
Silver	ppm	ASTM D5185(m)	>5	0	0	---
Aluminum	ppm	ASTM D5185(m)	>65	26	23	---
Lead	ppm	ASTM D5185(m)	>55	8	9	---
Copper	ppm	ASTM D5185(m)	>85	10	13	---
Tin	ppm	ASTM D5185(m)	>5	<1	<1	---
Antimony	ppm	ASTM D5185(m)		0	<1	---
Vanadium	ppm	ASTM D5185(m)		0	0	---
Beryllium	ppm	ASTM D5185(m)		0	0	---
Cadmium	ppm	ASTM D5185(m)		0	0	---

ADDITIVES		method	limit/base	current	history 1	history 2
Boron	ppm	ASTM D5185(m)	78	50	▲ 47	---
Barium	ppm	ASTM D5185(m)		0	0	---
Molybdenum	ppm	ASTM D5185(m)	0	<1	▲ 2	---
Manganese	ppm	ASTM D5185(m)		<1	<1	---
Magnesium	ppm	ASTM D5185(m)	0	6	▲ 13	---
Calcium	ppm	ASTM D5185(m)	113	120	▲ 130	---
Phosphorus	ppm	ASTM D5185(m)	222	212	▲ 201	---
Zinc	ppm	ASTM D5185(m)		15	▲ 26	---
Sulfur	ppm	ASTM D5185(m)	1326	1393	▲ 1387	---
Lithium	ppm	ASTM D5185(m)		<1	<1	---

CONTAMINANTS		method	limit/base	current	history 1	history 2
Silicon	ppm	ASTM D5185(m)	>20	8	9	---
Sodium	ppm	ASTM D5185(m)		8	10	---
Potassium	ppm	ASTM D5185(m)	>20	3	4	---

FLUID DEGRADATION		method	limit/base	current	history 1	history 2
Acid Number (AN)	mg KOH/g	ASTM D974*	1.4	1.47	---	---


OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history 1	history 2
White Metal	scalar	Visual*	NONE	NONE	---
Yellow Metal	scalar	Visual*	NONE	NONE	---
Precipitate	scalar	Visual*	NONE	NONE	---
Silt	scalar	Visual*	NONE	NONE	---
Debris	scalar	Visual*	NONE	NONE	---
Sand/Dirt	scalar	Visual*	NONE	NONE	---
Appearance	scalar	Visual*	NORML	NORML	---
Odor	scalar	Visual*	NORML	NORML	---
Emulsified Water	scalar	Visual*	>0.1	NEG	---
Free Water	scalar	Visual*		NEG	---

FLUID PROPERTIES	method	limit/base	current	history 1	history 2
Visc @ 40°C	cSt	ASTM D7279(m)	34.8	33.6 ▲	---
Visc @ 100°C	cSt	ASTM D7279(m)	7.0	6.5 ▲	---
Viscosity Index (VI)	Scale	ASTM D2270*	167	150	---

SAMPLE IMAGES	method	limit/base	current	history 1	history 2
Color					
Bottom					



GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PC0061457 **Received** : 05 Jul 2023
Lab Number : 02568024 **Diagnosed** : 05 Jul 2023
Unique Number : 5605070 **Diagnostician** : Kevin Marson
Test Package : IND 2 (Additional Tests: KV100, TAN Man, VI)

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

Metrobus Transit
 25 Messenger Drive
 St. John's, NL
 CA A1B 0H6
 Contact: Danny Oliver
 danny.oliver@metrobus.com
 T: (709)570-2025
 F: