


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
EBI DE COSTA RICA
Machine Id
VOLVO A30F A30F05
Component
2 Axle
Fluid
PETRO CANADA TRAXON 80W90 (--- LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PC0073897	PC0068834	---
Sample Date	Client Info		12 Apr 2023	04 Jan 2023	---
Machine Age	hrs	Client Info	13054	12561	---
Oil Age	hrs	Client Info	500	500	---
Oil Changed	Client Info		Changed	Changed	---
Sample Status			NORMAL	NORMAL	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m) >900	453	138	---
Chromium	ppm	ASTM D5185(m) >20	4	2	---
Nickel	ppm	ASTM D5185(m) >10	3	1	---
Titanium	ppm	ASTM D5185(m)	<1	1	---
Silver	ppm	ASTM D5185(m)	0	0	---
Aluminum	ppm	ASTM D5185(m) >30	1	12	---
Lead	ppm	ASTM D5185(m) >50	2	0	---
Copper	ppm	ASTM D5185(m) >150	76	6	---
Tin	ppm	ASTM D5185(m) >20	4	<1	---
Antimony	ppm	ASTM D5185(m) >5	0	0	---
Vanadium	ppm	ASTM D5185(m)	0	0	---
Beryllium	ppm	ASTM D5185(m)	0	0	---
Cadmium	ppm	ASTM D5185(m)	0	0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m) 243	235	219	---
Barium	ppm	ASTM D5185(m) 1	0	0	---
Molybdenum	ppm	ASTM D5185(m)	<1	<1	---
Manganese	ppm	ASTM D5185(m)	4	3	---
Magnesium	ppm	ASTM D5185(m) 2	2	12	---
Calcium	ppm	ASTM D5185(m) 6	17	59	---
Phosphorus	ppm	ASTM D5185(m) 987	1048	1051	---
Zinc	ppm	ASTM D5185(m) 1	13	34	---
Sulfur	ppm	ASTM D5185(m) 21530	18896	21652	---
Lithium	ppm	ASTM D5185(m)	<1	<1	---




CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >50	13	40	---
Sodium	ppm	ASTM D5185(m)	<1	5	---
Potassium	ppm	ASTM D5185(m) >20	2	3	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974* 1.9	1.39	1.44	---


OIL ANALYSIS REPORT










VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	VLITE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	141.0	134	165
Visc @ 100°C	cSt	ASTM D7279(m)	15.06	14.4	16.5
Viscosity Index (VI)	Scale	ASTM D2270*	108	106	105

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color					
Bottom					



GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **INDUSTRIAS del PETROLEO CANAD. SA**
Sample No. : PC0073897 **Received** : 13 Jul 2023 Contiguo FANAL, frente a la Autopista Bernardo Soto
Lab Number : 02569794 **Diagnosed** : 13 Jul 2023 Grecia, A
Unique Number : 5606840 **Diagnostician** : Wes Davis CR
Test Package : MOB 2 (Additional Tests: KV100, TAN Man, VI) Contact: Rodolfo Santamaria

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.