




OIL ANALYSIS REPORT

Sample Rating Trend

FUEL



Machine Id
701027
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (22 LTR)



DIAGNOSIS

Recommendation

The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

Fluid Condition

Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0086492	GFL0077205	GFL0077212
Sample Date	Client Info	14 Jul 2023	24 Apr 2023	23 Mar 2023
Machine Age	hrs	10267	86448	86448
Oil Age	hrs	0	0	0
Oil Changed	Client Info	Changed	Changed	Changed
Sample Status		ABNORMAL	NORMAL	NORMAL

WEAR METALS

method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m) >80	19	13	45
Chromium	ppm	ASTM D5185(m) >5	<1	<1	1
Nickel	ppm	ASTM D5185(m) >2	0	0	<1
Titanium	ppm	ASTM D5185(m)	0	<1	<1
Silver	ppm	ASTM D5185(m) >3	<1	0	0
Aluminum	ppm	ASTM D5185(m) >30	3	2	4
Lead	ppm	ASTM D5185(m) >30	0	0	0
Copper	ppm	ASTM D5185(m) >150	<1	<1	2
Tin	ppm	ASTM D5185(m) >5	0	0	<1
Antimony	ppm	ASTM D5185(m)	0	<1	0
Vanadium	ppm	ASTM D5185(m)	0	0	0
Beryllium	ppm	ASTM D5185(m)	0	0	0
Cadmium	ppm	ASTM D5185(m)	0	0	0

ADDITIVES

method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m) 0	10	7	6
Barium	ppm	ASTM D5185(m) 0	0	0	0
Molybdenum	ppm	ASTM D5185(m) 60	58	61	61
Manganese	ppm	ASTM D5185(m) 0	<1	<1	<1
Magnesium	ppm	ASTM D5185(m) 1010	899	960	910
Calcium	ppm	ASTM D5185(m) 1070	1005	1128	1196
Phosphorus	ppm	ASTM D5185(m) 1150	993	1103	1060
Zinc	ppm	ASTM D5185(m) 1270	1153	1209	1212
Sulfur	ppm	ASTM D5185(m) 2060	2307	2646	2341
Lithium	ppm	ASTM D5185(m)	<1	<1	<1

CONTAMINANTS

method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m) >20	7	3	6
Sodium	ppm	ASTM D5185(m)	21	8	21
Potassium	ppm	ASTM D5185(m) >20	7	<1	21
Fuel	%	ASTM D7593* >5	▲ 6.5	<1.0	<1.0
Glycol	%	ASTM D7922*	0.0	NEG	0.0

INFRA-RED




method	limit/base	current	history1	history2	
Soot %	%	ASTM D7844* >3	0.3	0.1	0.5
Nitration	Abs/cm	ASTM D7624* >20	10.9	7.6	13.4
Sulfation	Abs/.1mm	ASTM D7415* >30	22.0	19.4	29.3

FLUID DEGRADATION

method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	ASTM D7414* >25	20.6	15.8	27.8











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	15.4 ▲ 12.6	14.1	13.2

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0086492
Lab Number : 02570808
Unique Number : 5607854
Test Package : MOB 1 (Additional Tests: FuelDilution, Glycol, PercentFuel)

GFL Environmental - 217 - Aurora
 14131 BAYVIEW AVE, AURORA YARD
 AURORA, ON
 CA L4G 0K6
 Contact: Mike Havens
 MHavens@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
 F: (905)713-2445