



OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
WL0442
 Component
Rear Differential
 Fluid
PETRO CANADA PRODURO TO-4 SAE 30 (31 LTR)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: Oil might be different from what we are using .)

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0087339	---	---
Sample Date	Client Info		21 Jul 2023	---	---
Machine Age	hrs	Client Info	2232	---	---
Oil Age	hrs	Client Info	2232	---	---
Oil Changed	Client Info		Not Chngd	---	---
Sample Status			NORMAL	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m) >500	26	---	---
Chromium	ppm	ASTM D5185(m) >3	<1	---	---
Nickel	ppm	ASTM D5185(m) >3	0	---	---
Titanium	ppm	ASTM D5185(m) >2	<1	---	---
Silver	ppm	ASTM D5185(m) >2	0	---	---
Aluminum	ppm	ASTM D5185(m) >30	3	---	---
Lead	ppm	ASTM D5185(m) >13	0	---	---
Copper	ppm	ASTM D5185(m) >103	8	---	---
Tin	ppm	ASTM D5185(m) >5	0	---	---
Antimony	ppm	ASTM D5185(m) >5	0	---	---
Vanadium	ppm	ASTM D5185(m)	0	---	---
Beryllium	ppm	ASTM D5185(m)	0	---	---
Cadmium	ppm	ASTM D5185(m)	0	---	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m) 2	14	---	---
Barium	ppm	ASTM D5185(m) 0	0	---	---
Molybdenum	ppm	ASTM D5185(m) 0	3	---	---
Manganese	ppm	ASTM D5185(m) 9	<1	---	---
Magnesium	ppm	ASTM D5185(m) 1	56	---	---
Calcium	ppm	ASTM D5185(m) 3131	3008	---	---
Phosphorus	ppm	ASTM D5185(m) 1194	914	---	---
Zinc	ppm	ASTM D5185(m) 1281	1007	---	---
Sulfur	ppm	ASTM D5185(m) 3811	3572	---	---
Lithium	ppm	ASTM D5185(m)	<1	---	---

CONTAMINANTS


	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >100	6	---	---
Sodium	ppm	ASTM D5185(m)	<1	---	---
Potassium	ppm	ASTM D5185(m) >20	<1	---	---

VISUAL

	method	limit/base	current	history1	history2
White Metal	scalar	Visual* NONE	NONE	---	---
Yellow Metal	scalar	Visual* NONE	NONE	---	---
Precipitate	scalar	Visual* NONE	NONE	---	---
Silt	scalar	Visual* NONE	NONE	---	---
Debris	scalar	Visual* NONE	NONE	---	---
Sand/Dirt	scalar	Visual* NONE	NONE	---	---
Appearance	scalar	Visual* NORML	NORML	---	---
Odor	scalar	Visual* NORML	NORML	---	---
Emulsified Water	scalar	Visual* >.2	NEG	---	---
Free Water	scalar	Visual*	NEG	---	---











OIL ANALYSIS REPORT



FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	88.5	76.0	---	---

SAMPLE IMAGES		method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 GFL Environmental - 720 - Lafleche - Landfill
Sample No. : GFL0087339 **Received** : 26 Jul 2023
Lab Number : 02572471 **Diagnosed** : 27 Jul 2023
Unique Number : 5617522 **Diagnostician** : Kevin Marson
Test Package : MOB 1

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

17125 Lafleche Road,
 Moose Creek, ON
 CA K0C 1W0
 Contact: Charles Bergeron
 cbergeron@gflenv.com
 T: (613)538-4853
 F: