


Area  
**SHARP BUS LINES**  
Machine Id  
**INTERNATIONAL 4DRBUSKP4EB457128**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON HP 15W40 (--- GAL)**



**DIAGNOSIS**

**Recommendation**

We advise that you check the fuel injection system. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

**Wear**

All component wear rates are normal.

**Contamination**

There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

**Fluid Condition**

Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORMATION	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PC0081318</b>	---	---
Sample Date	Client Info		<b>26 Jul 2023</b>	---	---
Machine Age	kms	Client Info	<b>190213</b>	---	---
Oil Age	kms	Client Info	<b>5305</b>	---	---
Oil Changed	Client Info		<b>Changed</b>	---	---
Sample Status			<b>SEVERE</b>	---	---

CONTAMINATION	method	limit/base	current	history1	history2
Glycol	WC Method		<b>NEG</b>	---	---

WEAR METALS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m) >100	<b>19</b>	---	---
Chromium	ppm	ASTM D5185(m) >20	<b>&lt;1</b>	---	---
Nickel	ppm	ASTM D5185(m) >4	<b>0</b>	---	---
Titanium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Silver	ppm	ASTM D5185(m) >3	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185(m) >20	<b>6</b>	---	---
Lead	ppm	ASTM D5185(m) >40	<b>&lt;1</b>	---	---
Copper	ppm	ASTM D5185(m) >330	<b>&lt;1</b>	---	---
Tin	ppm	ASTM D5185(m) >15	<b>0</b>	---	---
Antimony	ppm	ASTM D5185(m)	<b>0</b>	---	---
Vanadium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Beryllium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Cadmium	ppm	ASTM D5185(m)	<b>0</b>	---	---




ADDITIVES	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m) 0	<b>6</b>	---	---
Barium	ppm	ASTM D5185(m) 0	<b>0</b>	---	---
Molybdenum	ppm	ASTM D5185(m) 60	<b>55</b>	---	---
Manganese	ppm	ASTM D5185(m) 0	<b>&lt;1</b>	---	---
Magnesium	ppm	ASTM D5185(m) 1010	<b>865</b>	---	---
Calcium	ppm	ASTM D5185(m) 1070	<b>910</b>	---	---
Phosphorus	ppm	ASTM D5185(m) 1150	<b>967</b>	---	---
Zinc	ppm	ASTM D5185(m) 1270	<b>1048</b>	---	---
Sulfur	ppm	ASTM D5185(m) 2060	<b>2369</b>	---	---
Lithium	ppm	ASTM D5185(m)	<b>&lt;1</b>	---	---

CONTAMINANTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >25	<b>3</b>	---	---
Sodium	ppm	ASTM D5185(m)	<b>2</b>	---	---
Potassium	ppm	ASTM D5185(m) >20	<b>4</b>	---	---
Fuel	%	ASTM D7593* >2.0	<b>7.1</b>	---	---

INFRA-RED	method	limit/base	current	history1	history2
Soot %	%	ASTM D7844* >3	<b>0.4</b>	---	---
Nitration	Abs/cm	ASTM D7624* >20	<b>8.5</b>	---	---
Sulfation	Abs/.1mm	ASTM D7415* >30	<b>20.4</b>	---	---

FLUID DEGRADATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414* >25	<b>15.5</b>	---	---









# OIL ANALYSIS REPORT



VISUAL		method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	---	---
Free Water	scalar	Visual*		<b>NEG</b>	---	---

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	118.2	<b>▲ 86.6</b>	---	---
Visc @ 100°C	cSt	ASTM D7279(m)	15.6	<b>▲ 12.6</b>	---	---
Viscosity Index (VI)	Scale	ASTM D2270*	139	<b>142</b>	---	---

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : PC0081318 **Received** : 02 Aug 2023  
**Lab Number** : **02573660** **Diagnosed** : 03 Aug 2023  
**Unique Number** : 5618711 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: FuelDilution, KV40, PercentFuel, VI )

**ICSB - Brantford**  
 567 Oak Park Rd.  
 Brantford, ON  
 CA N3T 5L8  
 Contact: Doug Hall  
 Djhall@sharpbus.com  
 T: (519)751-3434  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.