


Area  
**Aft Machinery Space [450175848]**  
Machine Id  
**Thruster Aft Starboard - Steering System (S/N Sample Tag CL-06003-S2)**  
Component  
**Hydraulic System**  
Fluid  
**PETRO CANADA HYDREX MV 36 (200 LTR)**



**DIAGNOSIS**

**Recommendation**  
Resample at the next service interval to monitor.

**Wear**  
All component wear rates are normal.

**Contamination**  
The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

**Fluid Condition**  
The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

**SAMPLE INFORMATION** method limit/base current history1 history2

Sample Number	Client Info	<b>PC</b>	PC0040118	PC0052442
Sample Date	Client Info	<b>19 Jul 2023</b>	11 Jun 2023	26 Apr 2023
Machine Age	hrs	Client Info	<b>0</b>	0
Oil Age	hrs	Client Info	<b>0</b>	0
Oil Changed	Client Info	<b>N/A</b>	N/A	N/A
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

**WEAR METALS** method limit/base current history1 history2

PQ	ASTM D8184*		<b>10</b>	0	0
Iron	ppm	ASTM D5185(m)	>20	<b>3</b>	3
Chromium	ppm	ASTM D5185(m)	>10	<b>0</b>	0
Nickel	ppm	ASTM D5185(m)	>10	<b>&lt;1</b>	<1
Titanium	ppm	ASTM D5185(m)		<b>0</b>	0
Silver	ppm	ASTM D5185(m)		<b>0</b>	0
Aluminum	ppm	ASTM D5185(m)	>10	<b>&lt;1</b>	<1
Lead	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	<1
Copper	ppm	ASTM D5185(m)	>20	<b>6</b>	7
Tin	ppm	ASTM D5185(m)	>10	<b>0</b>	0
Antimony	ppm	ASTM D5185(m)		<b>0</b>	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	0
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	0

**ADDITIVES** method limit/base current history1 history2






Boron	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	0
Barium	ppm	ASTM D5185(m)	0	<b>0</b>	0
Molybdenum	ppm	ASTM D5185(m)	0	<b>0</b>	0
Manganese	ppm	ASTM D5185(m)	1	<b>0</b>	0
Magnesium	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	<1
Calcium	ppm	ASTM D5185(m)	135	<b>69</b>	73
Phosphorus	ppm	ASTM D5185(m)	236	<b>334</b>	345
Zinc	ppm	ASTM D5185(m)	317	<b>377</b>	371
Sulfur	ppm	ASTM D5185(m)	561	<b>760</b>	768
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1

**CONTAMINANTS** method limit/base current history1 history2

Silicon	ppm	ASTM D5185(m)	>15	<b>&lt;1</b>	0
Sodium	ppm	ASTM D5185(m)		<b>0</b>	0
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	0

**FLUID CLEANLINESS** method limit/base current history1 history2

Particles >4µm	ASTM D7647		<b>1423</b>	2311	123
Particles >6µm	ASTM D7647	>1300	<b>271</b>	343	36
Particles >14µm	ASTM D7647	>160	<b>17</b>	14	6
Particles >21µm	ASTM D7647	>40	<b>5</b>	5	2
Particles >38µm	ASTM D7647	>10	<b>0</b>	1	1
Particles >71µm	ASTM D7647	>3	<b>0</b>	0	0
Oil Cleanliness	ISO 4406 (c)	>--/17/14	<b>18/15/11</b>	18/16/11	14/12/10




FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.40	<b>0.34</b>	0.46	0.41

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Precipitate	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Silt	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	Visual*	>0.05	<b>NEG</b>	NEG	NEG
Free Water	scalar	Visual*		<b>NEG</b>	NEG	NEG

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	32.25	<b>31.3</b>	31.5	31.5
Visc @ 100°C	cSt	ASTM D7279(m)	6.3	<b>6</b>	6.1	6
Viscosity Index (VI)	Scale	ASTM D2270*	148	<b>140</b>	144	139

### SAMPLE IMAGES



Color

Bottom



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : PC  
**Lab Number** : **02573744**  
**Unique Number** : 5618795  
**Test Package** : MAR 2 ( Additional Tests: KV100, PQ, VI )

**Suncor - Terra Nova Projects**  
 Scotia Centre, 235 Water Strret  
 St. John's, NL  
 CA A1C 1B6  
 Contact: Josh Hynes  
 joshynes@suncor.com  
 T: (709)778-3575  
 F: (709)724-2835

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.