




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
727003
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The water content is negligible. There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0090867	GFL0082546	GFL0078527
Sample Date	Client Info		02 Aug 2023	11 May 2023	11 Apr 2023
Machine Age	hrs	Client Info	0	36831	36733
Oil Age	hrs	Client Info	38853	0	0
Oil Changed	Client Info		Changed	N/A	N/A
Sample Status			NORMAL	ABNORMAL	ABNORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	▲ 2.7	▲ 5.1
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m) >120	13	4	16
Chromium	ppm	ASTM D5185(m) >20	<1	0	<1
Nickel	ppm	ASTM D5185(m) >5	0	<1	<1
Titanium	ppm	ASTM D5185(m) >2	0	<1	<1
Silver	ppm	ASTM D5185(m) >2	0	0	0
Aluminum	ppm	ASTM D5185(m) >20	1	<1	<1
Lead	ppm	ASTM D5185(m) >40	3	<1	3
Copper	ppm	ASTM D5185(m) >330	4	2	2
Tin	ppm	ASTM D5185(m) >15	0	0	<1
Antimony	ppm	ASTM D5185(m)	0	<1	<1
Vanadium	ppm	ASTM D5185(m)	0	0	0
Beryllium	ppm	ASTM D5185(m)	0	0	0
Cadmium	ppm	ASTM D5185(m)	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m) 0	4	▲ 50	2
Barium	ppm	ASTM D5185(m) 0	0	0	0
Molybdenum	ppm	ASTM D5185(m) 60	52	38	55
Manganese	ppm	ASTM D5185(m) 0	<1	<1	<1
Magnesium	ppm	ASTM D5185(m) 1010	856	▲ 473	922
Calcium	ppm	ASTM D5185(m) 1070	1004	▲ 1615	1078
Phosphorus	ppm	ASTM D5185(m) 1150	956	▲ 776	1046
Zinc	ppm	ASTM D5185(m) 1270	1061	▲ 830	1126
Sulfur	ppm	ASTM D5185(m) 2060	2316	2102	2507
Lithium	ppm	ASTM D5185(m)	<1	<1	<1

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >25	2	3	2
Sodium	ppm	ASTM D5185(m)	1	2	1
Potassium	ppm	ASTM D5185(m) >20	<1	0	0

INFRA-RED


	method	limit/base	current	history1	history2
Soot %	%	ASTM D7844* >4	3.2	0.5	2.7
Nitration	Abs/cm	ASTM D7624* >20	10.1	5.2	9.2
Sulfation	Abs/.1mm	ASTM D7415* >30	24.9	22.1	22.5

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414* >25	15.3	18.0	14.1











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	15.4	13.2 ▲	11.0 ▲

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **GFL Environmental - 246 - Windsor**
Sample No. : GFL0090867 **Received** : 08 Aug 2023 2700 Deziel Dr
Lab Number : 02574413 **Diagnosed** : 08 Aug 2023 Windsor, ON
Unique Number : 5619464 **Diagnostician** : Wes Davis CA N8W 5H8
Test Package : MOB 1

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.