



OIL ANALYSIS REPORT

Sample Rating Trend


NORMAL



Machine Id
429015

Component
Rear Differential

Fluid
GEAR OIL SAE 75W90 (--- GAL)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 75W90. Please confirm. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

The water content is negligible. There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0089767	---	---
Sample Date	Client Info		01 Aug 2023	---	---
Machine Age	kms	Client Info	883973	---	---
Oil Age	kms	Client Info	0	---	---
Oil Changed	Client Info		N/A	---	---
Sample Status			NORMAL	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m) >500	252	---	---
Chromium	ppm	ASTM D5185(m) >10	2	---	---
Nickel	ppm	ASTM D5185(m) >10	<1	---	---
Titanium	ppm	ASTM D5185(m)	<1	---	---
Silver	ppm	ASTM D5185(m)	<1	---	---
Aluminum	ppm	ASTM D5185(m) >25	12	---	---
Lead	ppm	ASTM D5185(m) >25	<1	---	---
Copper	ppm	ASTM D5185(m) >100	1	---	---
Tin	ppm	ASTM D5185(m) >10	0	---	---
Antimony	ppm	ASTM D5185(m) >5	3	---	---
Vanadium	ppm	ASTM D5185(m)	0	---	---
Beryllium	ppm	ASTM D5185(m)	0	---	---
Cadmium	ppm	ASTM D5185(m)	0	---	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m) 400	275	---	---
Barium	ppm	ASTM D5185(m) 200	<1	---	---
Molybdenum	ppm	ASTM D5185(m) 12	<1	---	---
Manganese	ppm	ASTM D5185(m)	5	---	---
Magnesium	ppm	ASTM D5185(m) 12	6	---	---
Calcium	ppm	ASTM D5185(m) 150	12	---	---
Phosphorus	ppm	ASTM D5185(m) 1650	1504	---	---
Zinc	ppm	ASTM D5185(m) 125	21	---	---
Sulfur	ppm	ASTM D5185(m) 22500	22424	---	---
Lithium	ppm	ASTM D5185(m)	<1	---	---

CONTAMINANTS


	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >75	40	---	---
Sodium	ppm	ASTM D5185(m)	5	---	---
Potassium	ppm	ASTM D5185(m) >20	3	---	---

VISUAL

	method	limit/base	current	history1	history2
White Metal	scalar	Visual* NONE	NONE	---	---
Yellow Metal	scalar	Visual* NONE	NONE	---	---
Precipitate	scalar	Visual* NONE	NONE	---	---
Silt	scalar	Visual* NONE	NONE	---	---
Debris	scalar	Visual* NONE	NONE	---	---
Sand/Dirt	scalar	Visual* NONE	NONE	---	---
Appearance	scalar	Visual* NORML	NORML	---	---
Odor	scalar	Visual* NORML	NORML	---	---
Emulsified Water	scalar	Visual* >.2	NEG	---	---
Free Water	scalar	Visual*	NEG	---	---










OIL ANALYSIS REPORT



FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	101	---	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **GFL Environmental - 582 - Nanaimo**
Sample No. : GFL0089767 **Received** : 09 Aug 2023
Lab Number : **02574902** **Diagnosed** : 09 Aug 2023
Unique Number : 5619953 **Diagnostician** : Wes Davis
Test Package : MOB 1

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

3469 Aqua Terra Rd.,
 Cassidy, BC
 CA V0R 1H0
 Contact: GFL Tech
 wcgfldemo@gmail.com
 T:
 F: