



OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
713069
Component
Transmission (Auto)
Fluid
DEXRON III (--- GAL)



DIAGNOSIS

Recommendation

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition. Le fluide n'était pas spécifié, toutefois, une comparaison avec d'autres fluides indiqua que ce fluide est du (GENERIC) DEXRON III. Veuillez confirmer.

Wear

Les taux d'usure de tous les composants sont normaux.

Contamination

Il n'y a aucun indice de contamination dans le fluide.

Fluid Condition

L'état de le fluide est acceptable pour la durée de service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0084449	---	---
Sample Date	Client Info		25 Jul 2023	---	---
Machine Age	kms	Client Info	9786	---	---
Oil Age	kms	Client Info	0	---	---
Oil Changed	Client Info		N/A	---	---
Sample Status			NORMAL	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m) >160	57	---	---
Chromium	ppm	ASTM D5185(m) >5	<1	---	---
Nickel	ppm	ASTM D5185(m) >5	<1	---	---
Titanium	ppm	ASTM D5185(m)	0	---	---
Silver	ppm	ASTM D5185(m) >5	0	---	---
Aluminum	ppm	ASTM D5185(m) >50	18	---	---
Lead	ppm	ASTM D5185(m) >50	18	---	---
Copper	ppm	ASTM D5185(m) >225	15	---	---
Tin	ppm	ASTM D5185(m) >10	2	---	---
Antimony	ppm	ASTM D5185(m)	0	---	---
Vanadium	ppm	ASTM D5185(m)	0	---	---
Beryllium	ppm	ASTM D5185(m)	0	---	---
Cadmium	ppm	ASTM D5185(m)	0	---	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	105	---	---
Barium	ppm	ASTM D5185(m)	<1	---	---
Molybdenum	ppm	ASTM D5185(m)	<1	---	---
Manganese	ppm	ASTM D5185(m)	2	---	---
Magnesium	ppm	ASTM D5185(m)	1	---	---
Calcium	ppm	ASTM D5185(m)	86	---	---
Phosphorus	ppm	ASTM D5185(m)	286	---	---
Zinc	ppm	ASTM D5185(m)	8	---	---
Sulfur	ppm	ASTM D5185(m)	1066	---	---
Lithium	ppm	ASTM D5185(m)	1	---	---

CONTAMINANTS


	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >20	7	---	---
Sodium	ppm	ASTM D5185(m)	5	---	---
Potassium	ppm	ASTM D5185(m) >20	4	---	---

VISUAL

	method	limit/base	current	history1	history2
White Metal	scalar	Visual* NONE	VLITE	---	---
Yellow Metal	scalar	Visual* NONE	NONE	---	---
Precipitate	scalar	Visual* NONE	NONE	---	---
Silt	scalar	Visual* NONE	VLITE	---	---
Debris	scalar	Visual* NONE	VLITE	---	---
Sand/Dirt	scalar	Visual* NONE	NONE	---	---
Appearance	scalar	Visual* NORML	NORML	---	---
Odor	scalar	Visual* NORML	NORML	---	---
Emulsified Water	scalar	Visual* >0.1	NEG	---	---
Free Water	scalar	Visual*	NEG	---	---



OIL ANALYSIS REPORT











FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	26.0	35.4	---	---

SAMPLE IMAGES		method	limit/base	current	history1	history2
---------------	--	--------	------------	---------	----------	----------

Color					no image	no image
Bottom					no image	no image

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 GFL Environmental - 780 - GMA - ICI - Solid Waste
Sample No. : GFL0084449 **Received** : 11 Aug 2023 4365 boul. St-Elzear Ouest,
Lab Number : 02575413 **Diagnosed** : 11 Aug 2023 Laval, QC
Unique Number : 5620464 **Diagnostician** : Wes Davis CA H7P 4J3
Test Package : MOB 1 Contact: Louis Michaud
louis.michaud@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.