




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
810050

Component
Diesel Engine

Fluid
DIESEL ENGINE OIL SAE 40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			GFL0062938	GFL0062921	GFL0041329
Sample Date	Client Info			17 Aug 2023	29 May 2023	07 Apr 2022
Machine Age	hrs	Client Info		3987	3433	597
Oil Age	hrs	Client Info		0	0	0
Oil Changed	Client Info			N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	<1.0
Glycol	WC Method			NEG	NEG	0.0

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>100	21	15	61
Chromium	ppm	ASTM D5185(m)	>20	1	<1	1
Nickel	ppm	ASTM D5185(m)	>4	0	<1	<1
Titanium	ppm	ASTM D5185(m)		0	<1	0
Silver	ppm	ASTM D5185(m)	>3	<1	0	<1
Aluminum	ppm	ASTM D5185(m)	>20	14	3	8
Lead	ppm	ASTM D5185(m)	>40	<1	<1	11
Copper	ppm	ASTM D5185(m)	>330	3	2	397
Tin	ppm	ASTM D5185(m)	>15	<1	<1	1
Antimony	ppm	ASTM D5185(m)		0	<1	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	250	5	9	113
Barium	ppm	ASTM D5185(m)	10	0	0	8
Molybdenum	ppm	ASTM D5185(m)	100	60	62	102
Manganese	ppm	ASTM D5185(m)		<1	<1	7
Magnesium	ppm	ASTM D5185(m)	450	978	964	768
Calcium	ppm	ASTM D5185(m)	3000	1087	1139	1456
Phosphorus	ppm	ASTM D5185(m)	1150	1038	1062	838
Zinc	ppm	ASTM D5185(m)	1350	1208	1185	992
Sulfur	ppm	ASTM D5185(m)	4250	2406	2527	2079
Lithium	ppm	ASTM D5185(m)		<1	<1	<1


CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>25	4	3	28
Sodium	ppm	ASTM D5185(m)	>216	9	7	5
Potassium	ppm	ASTM D5185(m)	>20	27	3	6

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>3	0.2	0.1	0
Nitration	Abs/cm	ASTM D7624*	>20	9.3	9.1	4.2
Sulfation	Abs/.1mm	ASTM D7415*	>30	21.6	20.4	15.2

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414*	>25	17.7	18.3	7.3











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	14.4	13.7	13.3

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 GFL Environmental - 777 - Belleville-Municipal waste
Sample No. : GFL0062938 **Received** : 22 Aug 2023 197 Putman Industrial Road
Lab Number : 02577374 **Diagnosed** : 22 Aug 2023 Belleville, ON
Unique Number : 5630434 **Diagnostician** : Wes Davis CA K8N 4Z6
Test Package : MOB 1

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

Contact: Andrea Michael
 amichael@gflenv.com
 T: (613)962-7144
 F: (613)962-1994