



OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
8286
 Component
Transmission (Auto)
 Fluid
ATF (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.
 Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition

The condition of the fluid is acceptable for the time in service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0091629	---	---
Sample Date	Client Info	25 Sep 2023	---	---
Machine Age	kms Client Info	502384	---	---
Oil Age	kms Client Info	0	---	---
Oil Changed	Client Info	N/A	---	---
Sample Status		NORMAL	---	---

WEAR METALS

method	limit/base	current	history1	history2
Iron ppm ASTM D5185(m)	>160	111	---	---
Chromium ppm ASTM D5185(m)	>5	0	---	---
Nickel ppm ASTM D5185(m)	>5	<1	---	---
Titanium ppm ASTM D5185(m)		0	---	---
Silver ppm ASTM D5185(m)	>5	<1	---	---
Aluminum ppm ASTM D5185(m)	>50	31	---	---
Lead ppm ASTM D5185(m)	>50	23	---	---
Copper ppm ASTM D5185(m)	>225	60	---	---
Tin ppm ASTM D5185(m)	>10	2	---	---
Antimony ppm ASTM D5185(m)		0	---	---
Vanadium ppm ASTM D5185(m)		0	---	---
Beryllium ppm ASTM D5185(m)		0	---	---
Cadmium ppm ASTM D5185(m)		0	---	---

ADDITIVES

method	limit/base	current	history1	history2
Boron ppm ASTM D5185(m)		184	---	---
Barium ppm ASTM D5185(m)		<1	---	---
Molybdenum ppm ASTM D5185(m)		0	---	---
Manganese ppm ASTM D5185(m)		<1	---	---
Magnesium ppm ASTM D5185(m)		3	---	---
Calcium ppm ASTM D5185(m)		153	---	---
Phosphorus ppm ASTM D5185(m)		481	---	---
Zinc ppm ASTM D5185(m)		16	---	---
Sulfur ppm ASTM D5185(m)		2636	---	---
Lithium ppm ASTM D5185(m)		<1	---	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon ppm ASTM D5185(m)	>20	9	---	---
Sodium ppm ASTM D5185(m)		11	---	---
Potassium ppm ASTM D5185(m)	>20	2	---	---

FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN) mg KOH/g ASTM D974*		2.39	---	---

