


Area  
**SHARP BUS LINES**  
Machine Id  
**INTERNATIONAL 1267**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON HP 15W40 (--- GAL)**



## DIAGNOSIS

### Recommendation

We advise that you check the fuel injection system. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

### Wear

Metal levels are typical for a new component breaking in.

### Contamination

There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

### Fluid Condition

Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PC0081537</b>	---	---
Sample Date	Client Info			<b>26 Sep 2023</b>	---	---
Machine Age	kms	Client Info		<b>234998</b>	---	---
Oil Age	kms	Client Info		<b>2000</b>	---	---
Oil Changed	Client Info			<b>Changed</b>	---	---
Sample Status				<b>SEVERE</b>	---	---

CONTAMINATION		method	limit/base	current	history1	history2
Glycol	WC Method			<b>NEG</b>	---	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>127	<b>19</b>	---	---
Chromium	ppm	ASTM D5185(m)	>3	<b>&lt;1</b>	---	---
Nickel	ppm	ASTM D5185(m)	>30	<b>&lt;1</b>	---	---
Titanium	ppm	ASTM D5185(m)	>2	<b>0</b>	---	---
Silver	ppm	ASTM D5185(m)	>2	<b>&lt;1</b>	---	---
Aluminum	ppm	ASTM D5185(m)	>59	<b>2</b>	---	---
Lead	ppm	ASTM D5185(m)	>29	<b>&lt;1</b>	---	---
Copper	ppm	ASTM D5185(m)	>135	<b>&lt;1</b>	---	---
Tin	ppm	ASTM D5185(m)	>2	<b>0</b>	---	---
Antimony	ppm	ASTM D5185(m)		<b>0</b>	---	---
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	---	---
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	---	---
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	---	---


ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	<b>1</b>	---	---
Barium	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	---	---
Molybdenum	ppm	ASTM D5185(m)	60	<b>56</b>	---	---
Manganese	ppm	ASTM D5185(m)	0	<b>0</b>	---	---
Magnesium	ppm	ASTM D5185(m)	1010	<b>877</b>	---	---
Calcium	ppm	ASTM D5185(m)	1070	<b>937</b>	---	---
Phosphorus	ppm	ASTM D5185(m)	1150	<b>905</b>	---	---
Zinc	ppm	ASTM D5185(m)	1270	<b>1069</b>	---	---
Sulfur	ppm	ASTM D5185(m)	2060	<b>2333</b>	---	---
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	---	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>18	<b>3</b>	---	---
Sodium	ppm	ASTM D5185(m)		<b>2</b>	---	---
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	---	---
Fuel	%	ASTM D7593*	>2.0	<b>7.4</b>	---	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>3	<b>0.9</b>	---	---
Nitration	Abs/cm	ASTM D7624*	>20	<b>8.7</b>	---	---
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>22.7</b>	---	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>19.8</b>	---	---











# OIL ANALYSIS REPORT



VISUAL		method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	---	---
Free Water	scalar	Visual*		<b>NEG</b>	---	---

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	118.2	<b>▲ 80.7</b>	---	---
Visc @ 100°C	cSt	ASTM D7279(m)	15.6	<b>▲ 12.3</b>	---	---
Viscosity Index (VI)	Scale	ASTM D2270*	139	<b>149</b>	---	---

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : PC0081537 **Received** : 13 Oct 2023  
**Lab Number** : **02588822** **Diagnosed** : 16 Oct 2023  
**Unique Number** : 5657888 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: FuelDilution, KV40, PercentFuel, VI )

**ICSB - Brantford**  
 567 Oak Park Rd.  
 Brantford, ON  
 CA N3T 5L8  
 Contact: Doug Hall  
 Djhall@sharpbus.com  
 T: (519)751-3434  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.