

OIL ANALYSIS REPORT

SHARP BUS LINES

Component

Diesel Engine

PETRO CANADA 15W40 (--- GAL)

INTERNATIONAL 1381

Sample Rating Trend





DIAGNOSIS

Recommendation

We advise that you check for the source of the coolant leak. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

Test for glycol is positive. There is a light concentration of glycol present in the oil.

Fluid Condition

The oil is no longer serviceable due to the presence of contaminants.

Sample Number Client Info PC0081418 Sample Date Client Info 28 Jul 2023 Machine Age kms Client Info 200214 Oil Age kms Client Info 2724 Oil Changed Client Info Changed Sample Status ABNORMAL CONTAMINATION method limit/base current history1 hi Fuel WC Method >2.0 <1.0	history2
Sample Number Client Info PC0081418 Sample Date Client Info 28 Jul 2023 Machine Age kms Client Info 200214 Oil Age kms Client Info Changed Oil Changed Client Info Changed Sample Status ABNORMAL CONTAMINATION method limit/base current history1 hi Fuel WC Method >2.0 <1.0 WEAR METALS method limit/base current history1 hi Iron ppm ASTM D5185(m) >127 28 Chromium ppm ASTM D5185(m) >3 1 Nickel ppm ASTM D5185(m) >3 1 Silver ppm ASTM D5185(m) >2 <1	istory2
Sample Number Client Info PC0081418 Sample Date Client Info 28 Jul 2023 Machine Age kms Client Info 200214 Oil Age kms Client Info Changed Oil Changed Client Info Changed Sample Status ABNORMAL CONTAMINATION method limit/base current history1 hi Fuel WC Method >2.0 <1.0 WEAR METALS method limit/base current history1 hi Iron ppm ASTM D5185(m) >127 28 Chromium ppm ASTM D5185(m) >3 1 Nickel ppm ASTM D5185(m) >3 1 Silver ppm ASTM D5185(m) >2 <1	istory2
Sample Date Client Info 28 Jul 2023 Machine Age kms Client Info 200214 Oil Age kms Client Info 2724 Oil Changed Client Info Changed Sample Status ABNORMAL CONTAMINATION method limit/base current history1 hi Fuel WC Method >2.0 <1.0	
Machine Age kms Client Info 200214 Oil Age kms Client Info 2724 Oil Changed Client Info Changed Sample Status ABNORMAL CONTAMINATION method limit/base current history1 hi Fuel WC Method >2.0 <1.0	
Oil Age kms Client Info 2724 Oil Changed Client Info Changed Sample Status ABNORMAL CONTAMINATION method limit/base current history1 hi Fuel WC Method >2.0 <1.0	
Oil Changed Sample Status Client Info Changed ABNORMAL CONTAMINATION method limit/base current history1 hit Fuel WC Method >2.0 <1.0 WEAR METALS method limit/base current history1 hi Iron ppm ASTM D5185(m) >127 28 Chromium ppm ASTM D5185(m) >3 1 Nickel ppm ASTM D5185(m) >30 <1 Silver ppm ASTM D5185(m) >2 0 Aluminum ppm ASTM D5185(m) >59 2 Copper ppm ASTM D5185(m) >135 1 Tin ppm ASTM D5185(m) >2 0	
Sample Status ABNORMAL CONTAMINATION method limit/base current history1 history2 <td></td>	
CONTAMINATION method limit/base current history1 hi Fuel WC Method >2.0 <1.0	
Fuel WC Method >2.0 <1.0 WEAR METALS method limit/base current history1 hi Iron ppm ASTM D5185(m) >127 28 Chromium ppm ASTM D5185(m) >3 1 Nickel ppm ASTM D5185(m) >2 0 Silver ppm ASTM D5185(m) >2 <1	
WEAR METALS method limit/base current history1 hi Iron ppm ASTM D5185(m) >127 28 Chromium ppm ASTM D5185(m) >3 1 Nickel ppm ASTM D5185(m) >30 <1	nistory2
Iron ppm ASTM D5185(m) >127 28 Chromium ppm ASTM D5185(m) >3 1 Nickel ppm ASTM D5185(m) >30 <1 Titanium ppm ASTM D5185(m) >2 0 Silver ppm ASTM D5185(m) >2 <1 Aluminum ppm ASTM D5185(m) >59 2 Lead ppm ASTM D5185(m) >29 <1 Copper ppm ASTM D5185(m) >135 1 Tin ppm ASTM D5185(m) >2 0	iistory2
Chromium ppm ASTM D5185(m) >3 1 Nickel ppm ASTM D5185(m) >30 <1	
Nickel ppm ASTM D5185(m) >30 <1 Titanium ppm ASTM D5185(m) >2 0 Silver ppm ASTM D5185(m) >2 <1	
Titanium ppm ASTM D5185(m) >2 0 Silver ppm ASTM D5185(m) >2 <1 Aluminum ppm ASTM D5185(m) >59 2 Lead ppm ASTM D5185(m) >29 <1 Copper ppm ASTM D5185(m) >135 1 Tin ppm ASTM D5185(m) >2 0	
Silver ppm ASTM D5185(m) >2 <1 Aluminum ppm ASTM D5185(m) >59 2 Lead ppm ASTM D5185(m) >29 <1 Copper ppm ASTM D5185(m) >135 1 Tin ppm ASTM D5185(m) >2 0	
Aluminum ppm ASTM D5185(m) >59 2 Lead ppm ASTM D5185(m) >29 <1 Copper ppm ASTM D5185(m) >135 1 Tin ppm ASTM D5185(m) >2 0	
Lead ppm ASTM D5185(m) >29 <1 Copper ppm ASTM D5185(m) >135 1 Tin ppm ASTM D5185(m) >2 0	
Lead ppm ASTM D5185(m) >29 <1 Copper ppm ASTM D5185(m) >135 1 Tin ppm ASTM D5185(m) >2 0	
Tin ppm ASTM D5185(m) >2 0	
Tin ppm ASTM D5185(m) >2 0	
Vanadium ppm ASTM D5185(m) 0	
Beryllium ppm ASTM D5185(m) 0	
Cadmium ppm ASTM D5185(m) 0	
ADDITIVES method limit/base current history1 hi	istory2
Boron ppm ASTM D5185(m) 4	
Barium ppm ASTM D5185(m) <1	
Molybdenum ppm ASTM D5185(m) 61	
Manganese ppm ASTM D5185(m) 0	
Magnesium ppm ASTM D5185(m) 910	
Calcium ppm ASTM D5185(m) 972	
Phosphorus ppm ASTM D5185(m) 966 Zinc ppm ASTM D5185(m) 1119	
Sulfur ppm ASTM D5185(m) 2454 Lithium ppm ASTM D5185(m) <1	
	istory2
Silicon ppm ASTM D5185(m) >18 9	. 5151 9 2
Sodium ppm ASTM D5185(m)	
Potassium ppm ASTM D5185(m) >20 ▲ 22	
Glycol	
	istory2
Soot %	
Nitration Abs/cm ASTM D7624* >20 7.4	
Sulfation Abs/.1mm ASTM D7415* >30 20.0	
	1-1- 0
FLUID DEGRADATION method limit/base current history1 hi	istory2

Oxidation

14.9



OIL ANALYSIS REPORT





CALA ISO 17025:2017 Accredited

Laboratory Sample No. Lab Number Unique Number

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : PC0081418

: 02589919

Received : 5658985

: 18 Oct 2023 Diagnosed : 19 Oct 2023 Diagnostician : Wes Davis Test Package : MOB 1 (Additional Tests: Glycol, KV40, VI)

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

ICSB - Brantford 567 Oak Park Rd. Brantford, ON CA N3T 5L8 Contact: Doug Hall Djhall@sharpbus.com T: (519)751-3434