

# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**SHARP BUS LINES**  
Machine Id  
**INTERNATIONAL 1108**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PC0081563</b>	---	---
Sample Date	Client Info			<b>11 Oct 2023</b>	---	---
Machine Age	kms	Client Info		<b>222158</b>	---	---
Oil Age	kms	Client Info		<b>2500</b>	---	---
Oil Changed	Client Info			<b>Changed</b>	---	---
Sample Status				<b>NORMAL</b>	---	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method		>2.0	<b>&lt;1.0</b>	---	---
Glycol	WC Method			<b>NEG</b>	---	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>127	<b>14</b>	---	---
Chromium	ppm	ASTM D5185(m)	>3	<b>0</b>	---	---
Nickel	ppm	ASTM D5185(m)	>30	<b>&lt;1</b>	---	---
Titanium	ppm	ASTM D5185(m)	>2	<b>0</b>	---	---
Silver	ppm	ASTM D5185(m)	>2	<b>&lt;1</b>	---	---
Aluminum	ppm	ASTM D5185(m)	>59	<b>4</b>	---	---
Lead	ppm	ASTM D5185(m)	>29	<b>&lt;1</b>	---	---
Copper	ppm	ASTM D5185(m)	>135	<b>&lt;1</b>	---	---
Tin	ppm	ASTM D5185(m)	>2	<b>0</b>	---	---
Antimony	ppm	ASTM D5185(m)		<b>0</b>	---	---
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	---	---
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	---	---
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	---	---



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<b>2</b>	---	---
Barium	ppm	ASTM D5185(m)		<b>&lt;1</b>	---	---
Molybdenum	ppm	ASTM D5185(m)		<b>56</b>	---	---
Manganese	ppm	ASTM D5185(m)		<b>0</b>	---	---
Magnesium	ppm	ASTM D5185(m)		<b>886</b>	---	---
Calcium	ppm	ASTM D5185(m)		<b>938</b>	---	---
Phosphorus	ppm	ASTM D5185(m)		<b>928</b>	---	---
Zinc	ppm	ASTM D5185(m)		<b>1077</b>	---	---
Sulfur	ppm	ASTM D5185(m)		<b>2342</b>	---	---
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	---	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>18	<b>3</b>	---	---
Sodium	ppm	ASTM D5185(m)		<b>8</b>	---	---
Potassium	ppm	ASTM D5185(m)	>20	<b>2</b>	---	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>3	<b>1</b>	---	---
Nitration	Abs/cm	ASTM D7624*	>20	<b>8.0</b>	---	---
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>21.0</b>	---	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>15.1</b>	---	---









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	---
Free Water	scalar	Visual*		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	85.6	---	---
Visc @ 100°C	cSt	ASTM D7279(m)	12.7	---	---
Viscosity Index (VI)	Scale	ASTM D2270*	146	---	---

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : PC0081563 **Received** : 23 Oct 2023  
**Lab Number** : 02590831 **Diagnosed** : 24 Oct 2023  
**Unique Number** : 5667910 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: KV40, VI )

**ICSB - Brantford**  
 567 Oak Park Rd.  
 Brantford, ON  
 CA N3T 5L8  
 Contact: Doug Hall  
 Djhall@sharpbus.com  
 T: (519)751-3434  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.