




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**801025**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (20 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0094179</b>	GFL	GFL0081996
Sample Date	Client Info		<b>17 Oct 2023</b>	15 Aug 2023	16 May 2023
Machine Age	hrs	Client Info	<b>81540</b>	0	81540
Oil Age	hrs	Client Info	<b>0</b>	0	6042
Oil Changed	Client Info		<b>Changed</b>	N/A	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>80	<b>31</b>	25	25
Chromium	ppm	ASTM D5185(m)	>5	<b>1</b>	1	1
Nickel	ppm	ASTM D5185(m)	>2	<b>0</b>	<1	<1
Titanium	ppm	ASTM D5185(m)		<b>0</b>	0	<1
Silver	ppm	ASTM D5185(m)	>3	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185(m)	>30	<b>2</b>	2	2
Lead	ppm	ASTM D5185(m)	>30	<b>&lt;1</b>	0	0
Copper	ppm	ASTM D5185(m)	>150	<b>&lt;1</b>	<1	2
Tin	ppm	ASTM D5185(m)	>5	<b>0</b>	0	0
Antimony	ppm	ASTM D5185(m)		<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)	0	<b>5</b>	5	7
Barium	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	0	0
Molybdenum	ppm	ASTM D5185(m)	60	<b>65</b>	63	63
Manganese	ppm	ASTM D5185(m)	0	<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185(m)	1010	<b>1035</b>	1018	955
Calcium	ppm	ASTM D5185(m)	1070	<b>1148</b>	1097	1148
Phosphorus	ppm	ASTM D5185(m)	1150	<b>1098</b>	1115	1072
Zinc	ppm	ASTM D5185(m)	1270	<b>1293</b>	1269	1212
Sulfur	ppm	ASTM D5185(m)	2060	<b>2460</b>	2501	2514
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1	<1

## CONTAMINANTS

	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>20	<b>4</b>	3	3
Sodium	ppm	ASTM D5185(m)		<b>6</b>	7	8
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	1	1

## INFRA-RED


	method	limit/base	current	history1	history2	
Soot %	%	ASTM D7844*	>3	<b>0.4</b>	0.4	0.4
Nitration	Abs/cm	ASTM D7624*	>20	<b>10.8</b>	11.1	12.2
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>22.8</b>	22.9	23.0

## FLUID DEGRADATION

	method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>19.7</b>	19.6	21.9











# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	15.4	14.5	14.6

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : GFL0094179  
**Lab Number** : 02590892  
**Unique Number** : 5667971  
**Test Package** : MOB 1

**GFL Environmental - 217 - Aurora**  
 14131 BAYVIEW AVE, AURORA YARD  
 AURORA, ON  
 CA L4G 0K6  
 Contact: Mike Havens  
 MHavens@gflenv.com  
 T:  
 F: (905)713-2445

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.