


Area
SHARP BUS LINES
Machine Id
INTERNATIONAL 1175
Component
Diesel Engine
Fluid
SAE 15W30 (--- GAL)



DIAGNOSIS

Recommendation
The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear
All component wear rates are normal.

Contamination
There is a moderate amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

Fluid Condition
The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PC0081397	PC0081327	---
Sample Date	Client Info			12 Oct 2023	21 Jul 2023	---
Machine Age	kms	Client Info		313589	309011	---
Oil Age	kms	Client Info		4500	13643	---
Oil Changed	Client Info			Changed	Changed	---
Sample Status				ABNORMAL	SEVERE	---

CONTAMINATION		method	limit/base	current	history1	history2
Glycol	WC Method			NEG	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>100	22	64	---
Chromium	ppm	ASTM D5185(m)	>20	<1	2	---
Nickel	ppm	ASTM D5185(m)	>4	<1	<1	---
Titanium	ppm	ASTM D5185(m)		0	0	---
Silver	ppm	ASTM D5185(m)	>3	<1	0	---
Aluminum	ppm	ASTM D5185(m)	>20	8	19	---
Lead	ppm	ASTM D5185(m)	>40	1	6	---
Copper	ppm	ASTM D5185(m)	>330	<1	1	---
Tin	ppm	ASTM D5185(m)	>15	0	<1	---
Antimony	ppm	ASTM D5185(m)		0	0	---
Vanadium	ppm	ASTM D5185(m)		0	0	---
Beryllium	ppm	ASTM D5185(m)		0	0	---
Cadmium	ppm	ASTM D5185(m)		0	0	---




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		3	7	---
Barium	ppm	ASTM D5185(m)		<1	0	---
Molybdenum	ppm	ASTM D5185(m)		55	51	---
Manganese	ppm	ASTM D5185(m)		0	<1	---
Magnesium	ppm	ASTM D5185(m)		865	797	---
Calcium	ppm	ASTM D5185(m)		983	873	---
Phosphorus	ppm	ASTM D5185(m)		905	888	---
Zinc	ppm	ASTM D5185(m)		1071	973	---
Sulfur	ppm	ASTM D5185(m)		2308	2124	---
Lithium	ppm	ASTM D5185(m)		<1	<1	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>25	3	5	---
Sodium	ppm	ASTM D5185(m)		2	3	---
Potassium	ppm	ASTM D5185(m)	>20	0	<1	---
Fuel	%	ASTM D7593*	>2.0	▲ 4.6	7.2	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>3	1.7	▲ 3.6	---
Nitration	Abs/cm	ASTM D7624*	>20	8.9	14.9	---
Sulfation	Abs/.1mm	ASTM D7415*	>30	23.5	32.1	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414*	>25	17.6	27.7	---









OIL ANALYSIS REPORT



VISUAL		method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	---
Free Water	scalar	Visual*		NEG	NEG	---

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	115	▲ 93.7	84.5	---
Visc @ 100°C	cSt	ASTM D7279(m)	11.0	▲ 13.5	12.7	---
Viscosity Index (VI)	Scale	ASTM D2270*	74	144	148	---

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PC0081397 **Received** : 30 Oct 2023
Lab Number : **02592820** **Diagnosed** : 31 Oct 2023
Unique Number : 5669899 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: KV40, PercentFuel, VI)

ICSB - Brantford
 567 Oak Park Rd.
 Brantford, ON
 CA N3T 5L8
 Contact: Doug Hall
 Djhall@sharpbus.com
 T: (519)751-3434
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.