


Machine Id
IHC 1015
Component
Diesel Engine
Fluid
PETRO CANADA 15W40 (12 GAL)



DIAGNOSIS

Recommendation
Resample at the next service interval to monitor.

Wear
Metal levels are typical for a new component breaking in.

Contamination
There is no indication of any contamination in the oil.

Fluid Condition
The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PC0071738	PC423493	PC423494
Sample Date	Client Info			21 Oct 2023	24 Aug 2023	04 Nov 2022
Machine Age	mls	Client Info		1825000	1819000	1875000
Oil Age	mls	Client Info		9000	9000	10000
Oil Changed	Client Info			Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>3.0		<1.0	<1.0	<1.0
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>165	6	7	11
Chromium	ppm	ASTM D5185(m)	>5	1	2	<1
Nickel	ppm	ASTM D5185(m)	>4	0	0	0
Titanium	ppm	ASTM D5185(m)	>2	0	<1	0
Silver	ppm	ASTM D5185(m)	>2	<1	0	0
Aluminum	ppm	ASTM D5185(m)	>20	<1	<1	<1
Lead	ppm	ASTM D5185(m)	>150	1	3	4
Copper	ppm	ASTM D5185(m)	>90	2	7	<1
Tin	ppm	ASTM D5185(m)	>5	<1	1	0
Antimony	ppm	ASTM D5185(m)		0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		1	2	2
Barium	ppm	ASTM D5185(m)		<1	1	0
Molybdenum	ppm	ASTM D5185(m)		60	59	59
Manganese	ppm	ASTM D5185(m)		0	<1	<1
Magnesium	ppm	ASTM D5185(m)		966	998	944
Calcium	ppm	ASTM D5185(m)		1051	1054	1050
Phosphorus	ppm	ASTM D5185(m)		1011	1088	1044
Zinc	ppm	ASTM D5185(m)		1194	1215	1150
Sulfur	ppm	ASTM D5185(m)		2591	2703	2566
Lithium	ppm	ASTM D5185(m)		<1	<1	<1

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>35	6	10	5
Sodium	ppm	ASTM D5185(m)		2	2	2
Potassium	ppm	ASTM D5185(m)	>20	0	<1	0

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>7.5	0.1	0.1	0.3
Nitration	Abs/cm	ASTM D7624*	>20	5.0	5.2	6.4
Sulfation	Abs/.1mm	ASTM D7415*	>30	18.6	19.8	20.5

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414*	>25	13.8	13.8	14.9









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	108	107	104
Visc @ 100°C	cSt	ASTM D7279(m)	14.4	14.3	14.2
Viscosity Index (VI)	Scale	ASTM D2270*	136	136	139

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PC0071738 **Received** : 01 Nov 2023
Lab Number : **02593138** **Diagnosed** : 01 Nov 2023
Unique Number : 5670217 **Diagnostician** : Kevin Marson
Test Package : MOB 1 (Additional Tests: KV40, VI)

RALPH C. ERICKSON
 12923 LONGWOODS RD
 THAMESVILLES, ON
 CA N0P 2K0
 Contact: RALPH ERICKSON
 trucker5429@hotmail.com
 T: (810)434-5429
 F: (519)692-9580

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.