




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
701041

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0085658	GFL0085682	GFL0070443
Sample Date	Client Info	06 Nov 2023	16 Aug 2023	17 May 2023
Machine Age	hrs	522	522	522
Oil Age	hrs	522	522	522
Oil Changed	Client Info	Changed	Changed	Changed
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	<1.0
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185(m) >100	8	17	12
Chromium	ppm ASTM D5185(m) >20	0	<1	<1
Nickel	ppm ASTM D5185(m) >4	<1	0	<1
Titanium	ppm ASTM D5185(m)	0	0	0
Silver	ppm ASTM D5185(m) >3	<1	<1	0
Aluminum	ppm ASTM D5185(m) >20	1	1	1
Lead	ppm ASTM D5185(m) >40	0	0	0
Copper	ppm ASTM D5185(m) >330	1	1	<1
Tin	ppm ASTM D5185(m) >15	0	0	0
Antimony	ppm ASTM D5185(m)	0	0	0
Vanadium	ppm ASTM D5185(m)	0	0	0
Beryllium	ppm ASTM D5185(m)	0	0	0
Cadmium	ppm ASTM D5185(m)	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185(m) 0	2	2	1
Barium	ppm ASTM D5185(m) 0	<1	0	0
Molybdenum	ppm ASTM D5185(m) 60	57	58	59
Manganese	ppm ASTM D5185(m) 0	0	<1	<1
Magnesium	ppm ASTM D5185(m) 1010	912	946	945
Calcium	ppm ASTM D5185(m) 1070	1016	1040	1077
Phosphorus	ppm ASTM D5185(m) 1150	921	1027	1040
Zinc	ppm ASTM D5185(m) 1270	1171	1195	1184
Sulfur	ppm ASTM D5185(m) 2060	2318	2376	2445
Lithium	ppm ASTM D5185(m)	<1	<1	<1

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185(m) >25	19	4	3
Sodium	ppm ASTM D5185(m)	2	2	2
Potassium	ppm ASTM D5185(m) >20	<1	2	0

INFRA-RED


method	limit/base	current	history1	history2
Soot %	% ASTM D7844* >3	0.2	0.4	0.3
Nitration	Abs/cm ASTM D7624* >20	9.2	10.6	9.8
Sulfation	Abs/.1mm ASTM D7415* >30	20.1	23.1	21.7

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm ASTM D7414* >25	16.8	19.4	18.8











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	15.4	13.6	13.4

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **GFL Environmental - 221 - Windsor**
Sample No. : GFL0085658 **Received** : 09 Nov 2023 **905 Tecumseh Road W**
Lab Number : 02595276 **Diagnosed** : 09 Nov 2023 **Windsor, ON**
Unique Number : 5672355 **Diagnostician** : Wes Davis **CA N8W 4J5**
Test Package : MOB 1 **Contact:** Rhys Marotte **rmarotte@gflenv.com**

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.