


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
Scoop 6 Yard
Machine Id
LHD6102
Component
Front Left Wheel Hub
Fluid
PETRO CANADA TRAXON 80W90 (4 LTR)



DIAGNOSIS

Recommendation

Confirm the source of the lubricant being utilized for top-up/fill. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

Additive levels indicate the addition of a different brand, or type of oil. The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PC0075091	PC0066828	---
Sample Date	Client Info		02 Nov 2023	11 May 2023	---
Machine Age	hrs	Client Info	3868	2662	---
Oil Age	hrs	Client Info	0	0	---
Oil Changed		Client Info	N/A	N/A	---
Sample Status			NORMAL	NORMAL	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m) >500	143	99	---
Chromium	ppm	ASTM D5185(m) >8	<1	<1	---
Nickel	ppm	ASTM D5185(m) >5	<1	<1	---
Titanium	ppm	ASTM D5185(m)	0	0	---
Silver	ppm	ASTM D5185(m)	<1	0	---
Aluminum	ppm	ASTM D5185(m) >5	<1	<1	---
Lead	ppm	ASTM D5185(m) >5	0	<1	---
Copper	ppm	ASTM D5185(m) >50	8	19	---
Tin	ppm	ASTM D5185(m)	0	<1	---
Antimony	ppm	ASTM D5185(m) >5	0	0	---
Vanadium	ppm	ASTM D5185(m)	0	0	---
Beryllium	ppm	ASTM D5185(m)	0	0	---
Cadmium	ppm	ASTM D5185(m)	0	0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m) 243	6	31	---
Barium	ppm	ASTM D5185(m) 1	4	0	---
Molybdenum	ppm	ASTM D5185(m)	0	<1	---
Manganese	ppm	ASTM D5185(m)	1	1	---
Magnesium	ppm	ASTM D5185(m) 2	<1	3	---
Calcium	ppm	ASTM D5185(m) 6	23	32	---
Phosphorus	ppm	ASTM D5185(m) 987	634	841	---
Zinc	ppm	ASTM D5185(m) 1	17	18	---
Sulfur	ppm	ASTM D5185(m) 21530	22458	21447	---
Lithium	ppm	ASTM D5185(m)	<1	<1	---




CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >25	3	3	---
Sodium	ppm	ASTM D5185(m)	<1	<1	---
Potassium	ppm	ASTM D5185(m) >20	0	<1	---

VISUAL

	method	limit/base	current	history1	history2
White Metal	scalar	Visual* NONE	NONE	VLITE	---
Yellow Metal	scalar	Visual* NONE	NONE	NONE	---
Precipitate	scalar	Visual* NONE	NONE	NONE	---
Silt	scalar	Visual* NONE	NONE	NONE	---
Debris	scalar	Visual* NONE	NONE	NONE	---
Sand/Dirt	scalar	Visual* NONE	NONE	NONE	---
Appearance	scalar	Visual* NORML	NORML	NORML	---
Odor	scalar	Visual* NORML	NORML	NORML	---
Emulsified Water	scalar	Visual* >0.2	NEG	NEG	---
Free Water	scalar	Visual*	NEG	NEG	---









OIL ANALYSIS REPORT



FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	141.0	139	138	---
Visc @ 100°C	cSt	ASTM D7279(m)	15.06	14.5	14.5	---
Viscosity Index (VI)	Scale	ASTM D2270*	108	102	103	---

SAMPLE IMAGES		method	limit/base	current	history1	history2
Color						no image
Bottom						no image

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PC0075091 **Received** : 14 Nov 2023
Lab Number : 02596311 **Diagnosed** : 14 Nov 2023
Unique Number : 5681391 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: KV100, VI)

Lakeshore Gold Timmins West
 Timmins, ON
 CA
 Contact: Adam Koscielak
 adam.koscielak@HFSinclair.com
 T:
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.