




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
413153
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (--- LTR)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0097619	GFL0090609	---
Sample Date	Client Info		10 Nov 2023	24 Aug 2023	---
Machine Age	hrs	Client Info	1674	1115	---
Oil Age	hrs	Client Info	559	0	---
Oil Changed	Client Info		Changed	N/A	---
Sample Status			NORMAL	ABNORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	<1.0	---
Water	WC Method	>0.2	NEG	NEG	---
Glycol	WC Method		NEG	NEG	---

WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>120	18	24	---
Chromium	ppm	ASTM D5185(m)	>20	<1	<1	---
Nickel	ppm	ASTM D5185(m)	>5	<1	1	---
Titanium	ppm	ASTM D5185(m)	>2	0	0	---
Silver	ppm	ASTM D5185(m)	>2	<1	2	---
Aluminum	ppm	ASTM D5185(m)	>20	3	5	---
Lead	ppm	ASTM D5185(m)	>40	4	14	---
Copper	ppm	ASTM D5185(m)	>330	178	508	---
Tin	ppm	ASTM D5185(m)	>15	<1	1	---
Antimony	ppm	ASTM D5185(m)		0	0	---
Vanadium	ppm	ASTM D5185(m)		0	0	---
Beryllium	ppm	ASTM D5185(m)		0	0	---
Cadmium	ppm	ASTM D5185(m)		0	0	---

ADDITIVES

	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)	2	4	14	---
Barium	ppm	ASTM D5185(m)	0	<1	0	---
Molybdenum	ppm	ASTM D5185(m)	50	62	66	---
Manganese	ppm	ASTM D5185(m)	0	<1	2	---
Magnesium	ppm	ASTM D5185(m)	950	991	938	---
Calcium	ppm	ASTM D5185(m)	1050	1095	1082	---
Phosphorus	ppm	ASTM D5185(m)	995	977	1004	---
Zinc	ppm	ASTM D5185(m)	1180	1201	1109	---
Sulfur	ppm	ASTM D5185(m)	2600	2775	2199	---
Lithium	ppm	ASTM D5185(m)		<1	<1	---

CONTAMINANTS


	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>25	5	14	---
Sodium	ppm	ASTM D5185(m)		2	2	---
Potassium	ppm	ASTM D5185(m)	>20	4	12	---

INFRA-RED

	method	limit/base	current	history1	history2	
Soot %	%	ASTM D7844*	>4	0.3	0.3	---
Nitration	Abs/cm	ASTM D7624*	>20	8.2	8.9	---
Sulfation	Abs./1mm	ASTM D7415*	>30	20.3	21.7	---



OIL ANALYSIS REPORT



FLUID DEGRADATION

	method	limit/base	current	history1	history2	
Oxidation	Abs./1mm	ASTM D7414*	>25	16.0	17.0	---









VISUAL

	method	limit/base	current	history1	history2	
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	---
Free Water	scalar	Visual*		NEG	NEG	---

FLUID PROPERTIES

	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D7279(m)	12.00	11.1	11.0	---

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **GFL Environmental - 554 - Edmonton SW**
Sample No. : GFL0097619 **Received** : 21 Nov 2023 **8409 -15th Street NW**
Lab Number : **02597800** **Diagnosed** : 21 Nov 2023 **Edmonton, AB**
Unique Number : 5682880 **Diagnostician** : Wes Davis **CA T6P 0B8**
Test Package : MOB 1 **Contact:** Tim Greig
tgreig@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.