

GREASE ANALYSIS

Sample Rating Trend



AFTER GREASE

Grease

Fluid PETRO CANADA PRECISION XL EP2 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Grease Condition

The condition of the grease is acceptable for the time in service.


Contaminants

There is no indication of any contamination in the grease.

| , | | | | Nov2023 | | |
|------------------|------------|---------------|------------|-------------|----------|----------|
| SAMPLE INFORM | ATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | PC | | |
| Sample Date | | Client Info | | 26 Nov 2023 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Grease Age | hrs | Client Info | | 0 | | |
| Grease Serviced | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATIO | DN | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| PQ | | ASTM D8184* | >200 | 1110 | | |
| Iron | ppm | ASTM D5185(m) | >250 | 85 | | |
| Chromium | ppm | ASTM D5185(m) | >10 | <1 | | |
| Nickel | ppm | ASTM D5185(m) | >5 | 2 | | |
| Cadmium | ppm | ASTM D5185(m) | | 0 | | |
| Titanium | ppm | ASTM D5185(m) | | 0 | | |
| Vanadium | ppm | ASTM D5185(m) | | 0 | | |
| Lead | ppm | ASTM D5185(m) | >25 | 6 | | |
| Copper | ppm | ASTM D5185(m) | >75 | <1 | | |
| Tin | ppm | ASTM D5185(m) | >5 | 0 | | |
| Silver | ppm | ASTM D5185(m) | >5 | <1 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185(m) | | 3 | | |
| Magnesium | ppm | ASTM D5185(m) | | 11 | | |
| Manganese | ppm | ASTM D5185(m) | | <1 | | |
| Molybdenum | ppm | ASTM D5185(m) | | 162 | | |
| Phosphorus | ppm | ASTM D5185(m) | | 59 | | |
| Zinc | ppm | ASTM D5185(m) | | 52 | | |
| Antimony | ppm | ASTM D5185(m) | | 23 | | |
| THICKENER/SC |)AP | method | limit/base | current | history1 | history2 |
| Aluminum | ppm | ASTM D5185(m) | | 2 | | |
| Barium | ppm | ASTM D5185(m) | | 3 | | |
| Calcium | ppm | ASTM D5185(m) | | 144 | | |
| Sodium | ppm | ASTM D5185(m) | | 61 | | |
| Lithium | ppm | ASTM D5185(m) | | 200 | | |
| Sulfur | ppm | ASTM D5185(m) | | 614 | | |
| CONTAMINANT | S | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185(m) | >150 | 3 | | |
| | ppm | ASTM D5185(m) | | 3 | | |
| GREASE COND | ITION | method | limit/base | current | history1 | history2 |
| Grease Color | | Visual* | Brown | Green | | |
| Texture | | In-house* | Stringy | Short fiber | | |
| NLGI Consistency | NLGI Scale | SKF Method* | 2 | 1-2 | | |
| | | | | | | |



GREASE ANALYSIS



| SAMPLE IMAGES method lim | it/base | current | history1 | history2 |
|--------------------------|-------------------------|----------|----------|----------|
| Color | | | no image | no image |
| Bottom | | | no image | no image |
| PrtFilter | | | no image | no image |
| GRAPHS | | | | |
| Ferrous Alloys | | PQ | | |
| iron | 1150 1100 | | | |
| non ium nickel | 1050 | | | |
| | 1000 | | | |
| + | 950 | | | |
| | 900 850 | 1 | | |
| + | 800 | | | |
| | 750 | | | |
| | 700 | | | |
| Nov26/23 | 650 | | | |
| | 문 ⁶⁰⁰ 550 | | | |
| Non-ferrous Metals | 500 | | | |
| copper | 450 | P | | |
| † tin | 400 | Severe | | |
| | 350 300 | | | |
| | 250 | | | |
| | 200 | Abnormal | | |
| | 150 | | | |
| | 100 50 | | | |
| | 0 | | | |
| Nov26/23 | | Nov26/23 | | |
| 2 2 | | No | | |



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 CALA Sample No. : PC Received : 27 Nov 2023 Lab Number : 02599171 Diagnosed : 29 Nov 2023 ISO 17025:2017 Accredited Laboratory Unique Number : 5684251 Diagnostician : Bill Quesnel **Test Package** : GRS 1 (Additional Tests: BottomAnalysis) To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Suncor - Terra Nova Projects Scotia Centre, 235 Water Strret St. John`s, NL CA A1C 1B6 Contact: Deanne Badcock dbadcock@suncor.com T: (709)778-3843 F: (709)724-2784