



OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
EX0300
Component
Rear Right Planetary
Fluid
NOT GIVEN (--- GAL)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is SAE 50 Gear Oil. Please confirm the oil type and grade, and specify the brand of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0094024	---	---
Sample Date	Client Info		27 Nov 2023	---	---
Machine Age	hrs	Client Info	2019	---	---
Oil Age	hrs	Client Info	7	---	---
Oil Changed	Client Info		Changed	---	---
Sample Status			NORMAL	---	---

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	NEG	---	---

WEAR METALS

	method	limit/base	current	history1	history2
PQ	ASTM D8184*		152	---	---
Iron	ppm	ASTM D5185(m) >500	937	---	---
Chromium	ppm	ASTM D5185(m) >10	13	---	---
Nickel	ppm	ASTM D5185(m) >10	12	---	---
Titanium	ppm	ASTM D5185(m)	13	---	---
Silver	ppm	ASTM D5185(m)	<1	---	---
Aluminum	ppm	ASTM D5185(m) >25	190	---	---
Lead	ppm	ASTM D5185(m) >25	1	---	---
Copper	ppm	ASTM D5185(m) >75	3	---	---
Tin	ppm	ASTM D5185(m) >10	0	---	---
Antimony	ppm	ASTM D5185(m) >5	3	---	---
Vanadium	ppm	ASTM D5185(m)	<1	---	---
Beryllium	ppm	ASTM D5185(m)	0	---	---
Cadmium	ppm	ASTM D5185(m)	0	---	---

ADDITIVES


	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	164	---	---
Barium	ppm	ASTM D5185(m)	2	---	---
Molybdenum	ppm	ASTM D5185(m)	0	---	---
Manganese	ppm	ASTM D5185(m)	16	---	---
Magnesium	ppm	ASTM D5185(m)	30	---	---
Calcium	ppm	ASTM D5185(m)	44	---	---
Phosphorus	ppm	ASTM D5185(m)	954	---	---
Zinc	ppm	ASTM D5185(m)	29	---	---
Sulfur	ppm	ASTM D5185(m)	17635	---	---
Lithium	ppm	ASTM D5185(m)	<1	---	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >75	647	---	---
Sodium	ppm	ASTM D5185(m)	32	---	---
Potassium	ppm	ASTM D5185(m) >20	78	---	---



OIL ANALYSIS REPORT




VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	Visual*	NONE	NONE	---	---
Yellow Metal	scalar	Visual*	NONE	NONE	---	---
Precipitate	scalar	Visual*	NONE	NONE	---	---
Silt	scalar	Visual*	NONE	NONE	---	---
Debris	scalar	Visual*	NONE	NONE	---	---
Sand/Dirt	scalar	Visual*	NONE	NONE	---	---
Appearance	scalar	Visual*	NORML	NORML	---	---
Odor	scalar	Visual*	NORML	NORML	---	---
Emulsified Water	scalar	Visual*	>0.2	NEG	---	---
Free Water	scalar	Visual*		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	134	---	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------

Color				no image	no image
Bottom				no image	no image

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **GFL Environmental - 968 - Boylston**
Sample No. : GFL0094024 **Received** : 08 Dec 2023 151 Waste Management Road Hiwy 16
Lab Number : **02601959** **Diagnosed** : 11 Dec 2023 Boylston, NS
Unique Number : 5695044 **Diagnostician** : Wes Davis CA B0H 1G0
Test Package : MOB 1 (Additional Tests: PQ) Contact: Bruce Avery
 bruce.avery@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.