



# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**4518**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SAE 10W30 (--- GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0101732</b>	---	---
Sample Date	Client Info		<b>24 Nov 2023</b>	---	---
Machine Age	hrs	Client Info	<b>31766</b>	---	---
Oil Age	hrs	Client Info	<b>0</b>	---	---
Oil Changed	Client Info		<b>Changed</b>	---	---
Sample Status			<b>NORMAL</b>	---	---

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	---	---
Water	WC Method	>0.2	<b>NEG</b>	---	---
Glycol	WC Method		<b>NEG</b>	---	---

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m) >100	<b>20</b>	---	---
Chromium	ppm	ASTM D5185(m) >20	<b>&lt;1</b>	---	---
Nickel	ppm	ASTM D5185(m) >4	<b>&lt;1</b>	---	---
Titanium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Silver	ppm	ASTM D5185(m) >3	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185(m) >20	<b>2</b>	---	---
Lead	ppm	ASTM D5185(m) >40	<b>4</b>	---	---
Copper	ppm	ASTM D5185(m) >330	<b>1</b>	---	---
Tin	ppm	ASTM D5185(m) >15	<b>&lt;1</b>	---	---
Antimony	ppm	ASTM D5185(m)	<b>0</b>	---	---
Vanadium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Beryllium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Cadmium	ppm	ASTM D5185(m)	<b>0</b>	---	---

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m) 1	<b>2</b>	---	---
Barium	ppm	ASTM D5185(m) 1	<b>0</b>	---	---
Molybdenum	ppm	ASTM D5185(m) 1	<b>60</b>	---	---
Manganese	ppm	ASTM D5185(m) 1	<b>0</b>	---	---
Magnesium	ppm	ASTM D5185(m) 10	<b>964</b>	---	---
Calcium	ppm	ASTM D5185(m) 2942	<b>1044</b>	---	---
Phosphorus	ppm	ASTM D5185(m) 1102	<b>980</b>	---	---
Zinc	ppm	ASTM D5185(m) 1351	<b>1167</b>	---	---
Sulfur	ppm	ASTM D5185(m) 3903	<b>2474</b>	---	---
Lithium	ppm	ASTM D5185(m)	<b>&lt;1</b>	---	---

## CONTAMINANTS



	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >25	<b>2</b>	---	---
Sodium	ppm	ASTM D5185(m)	<b>2</b>	---	---
Potassium	ppm	ASTM D5185(m) >20	<b>1</b>	---	---

## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	ASTM D7844* >3	<b>0.7</b>	---	---
Nitration	Abs/cm	ASTM D7624* >20	<b>7.6</b>	---	---
Sulfation	Abs/.1mm	ASTM D7415* >30	<b>21.2</b>	---	---



# OIL ANALYSIS REPORT











FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs./1mm	ASTM D7414*	>25	<b>16.9</b>	---	---

VISUAL		method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	---	---
Free Water	scalar	Visual*		<b>NEG</b>	---	---

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	74.0	<b>71.0</b>	---	---
Visc @ 100°C	cSt	ASTM D7279(m)	11.4	<b>11.1</b>	---	---
Viscosity Index (VI)	Scale	ASTM D2270*	146	<b>147</b>	---	---

## GRAPHS



ISO 17025:2017  
Accredited  
Laboratory

**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 GFL Environmental - 554 - Edmonton SW  
**Sample No.** : GFL0101732 **Received** : 11 Dec 2023  
**Lab Number** : 02602117 **Diagnosed** : 11 Dec 2023  
**Unique Number** : 5695202 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: KV40, VI )

8409 -15th Street NW  
Edmonton, AB  
CA T6P 0B8  
Contact: Tim Greig  
tgreig@gflenv.com  
T: (780)231-0521  
F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.