


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id 910075

Component **Diesel Engine** Fluid

CASTROL TECTION EXTRA SAE 15W-40 (--- LTR)

DIAGNOSIS	SAMPLE INFORM		method	limit/base	current	history1	history2
Recommendation	Sample Number		Client Info		GFL0086776	GFL0042860	GFL0042880
The oil change at the time of sampling has been	Sample Date		Client Info		22 Dec 2023	03 Oct 2023	25 May 2022
noted. We recommend an early resample to	Machine Age	hrs	Client Info		7519	0	71518
monitor this condition.	Oil Age	hrs	Client Info		600	0	4055
Wear	Oil Changed		Client Info		Changed	N/A	Changed
All component wear rates are normal.	Sample Status				ABNORMAL	NORMAL	NORMAL
Contamination	·						
There is a moderate amount of fuel present in the	CONTAMINATI	ON	method	limit/base	current	history1	history2
oil. Tests confirm the presence of fuel in the oil.	Water		WC Method	>0.2	NEG	NEG	NEG
Fluid Condition	Glycol		WC Method		NEG	NEG	NEG
Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the	WEAR METALS	S	method	limit/base	current	history1	history2
presence of contaminants.	Iron	ppm	ASTM D5185(m)	>120	6	8	10
•	Chromium	ppm	ASTM D5185(m)		0	0	<1
	Nickel	ppm	ASTM D5185(m)		<1	0	<1
	Titanium	ppm	ASTM D5185(m)		0	0	0
	Silver	ppm	ASTM D5185(m)		0	<1	0
	Aluminum	ppm	ASTM D5185(m)		3	3	3
	Lead	ppm	ASTM D5185(m)		<1	3	<1
	Copper	ppm	ASTM D5185(m)		<1	1	2
	Tin	ppm	ASTM D5185(m)		0	<1	<1
	Antimony	ppm	ASTM D5185(m)		0	0	<1
	Vanadium	ppm	ASTM D5185(m)		0	0	0
	Beryllium	ppm	ASTM D5185(m)		0	0	0
	Cadmium	ppm	ASTM D5185(m)		0	0	0
	ADDITIVES		method	limit/base	current	history1	history2
						18	36
	Boron	ppm	ASTM D5185(m)	30	33		
	Barium	ppm	ASTM D5185(m)		0	<1 81	0 88
	Molybdenum	ppm	ASTM D5185(m)		83		
	Manganese Magnesium	ppm	ASTM D5185(m)	110	0 61	0 33	<1 34
	Calcium	ppm	ASTM D5185(m) ASTM D5185(m)		2025	2164	34 2114
		ppm	()	2740 1240	2025 912	933	1006
	Phosphorus Zinc	ppm	ASTM D5185(m) ASTM D5185(m)		912 1078	933 1145	1167
	Sulfur	ppm	ASTM D5185(m) ASTM D5185(m)		1078 2963	2839	2961
	Lithium	ppm	ASTM D5185(m) ASTM D5185(m)	3520	2963 <1	2839 <1	2961
		ppm					
	CONTAMINAN	IS	method	limit/base		history1	history2
	Silicon	ppm	ASTM D5185(m)	>25	3	3	5
	Sodium	ppm	ASTM D5185(m)		3	5	5
	Potassium	ppm	ASTM D5185(m)		2	1	1
	Fuel	%	ASTM D7593*	>3.0	<u> </u>	<1.0	<1.0
	INFRA-RED		method	limit/base	current	history1	history2
	Soot %	%	ASTM D7844*	>4	0.3	0.4	0.3
	Nitration		ASTM D7624*	>20	9.5	9.5	9.6
	Sulfation	Abc/1mm	ASTM D7/15*	> 20	10.7	21.2	21.5

Abs/.1mm ASTM D7415* >30

19.7


Sulfation

21.5

21.2



OIL ANALYSIS REPORT



	FLUID DEGRAD		method	limit/base	current	history1	history2
	Oxidation	Abs/.1mm	ASTM D7414*	>25	14.3	15.7	14.7
1	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	Visual*	NONE	NONE	VLITE	
	Yellow Metal	scalar	Visual*	NONE	NONE	NONE	
-	Precipitate	scalar	Visual*	NONE	NONE	NONE	
Ĩ	Silt	scalar	Visual*	NONE	NONE	NONE	
Dec/2/23	Debris	scalar	Visual*	NONE	NONE	NONE	
	Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	
	Appearance	scalar	Visual*	NORML	NORML	NORML	
	Odor Emulsified Water	scalar scalar	Visual* Visual*	NORML >0.2	NORML NEG	NORML	NORML
	Free Water	scalar	Visual*	>0.2	NEG	NEG	NEG
	FLUID PROPE		method	limit/base	current	history1	history2
	Visc @ 100°C	cSt	ASTM D7279(m)		12.2	13.4	13.8
2	GRAPHS						
522/23	Iron (ppm)			10	Lead (ppm)		
	Severe	1	1	8	Smuoro		
bpm	200			E 60			
	100 - Abnormal						
				2			
	May19/21 Sep29/21	Mar7/22 .	May25/22 . 0ct3/23 .	Dec22/23	May19/21 Sep29/21	Dec7/21. Mar7/22 -	May25/22 . 0ct3/23 .
	May Sep	Ma	Mayi	Deci	Sep	Ma Ma	Mayû Oc
	Aluminum (ppm)			51	Chromium (opm)	
	40 - Severe			41	0		
a,	30 - 20 - Abnormal			E 31	0 Abaamat		
,		1					
				10			
	May19/21 Sep29/21	Mar7/22 .	May25/22 . 0ct3/23 .	Dec22/23	May19/21. Sep29/21.	Dec7/21. Mar7/22 -	May25/22 . 0ct3/23 .
		Ma	May	Dec	-	_	May
3	Copper (ppm)			80	Silicon (ppm)	
	300 -			60			
bpm	200 -			E 4	Abnormal		
	100-			2	D - 9		
		723 -	723			22	22
	May19/21 Sep29/21 Dec7/21	Mar7/22	May25/22 0ct3/23	Dec22/23	May19/21 Sep29/21	Dec7/21 Mar7/22	May25/22 0ct3/23
	▲ Viscosity @ 100°C		~	_	Fuel Dilution		~
	20 18 Abnormal			6.0		·,	,,
J-U-U					T I		
CS+ /100-0	14 Abnormal				0		/
		Mar7/22 -	May25/22 - 0ct3/23 -	Dec22/23	May19/21	Dec7/21. Mar7/22 -	May25/22
	May19/21 Sep29/21 Dec7/21						- H

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Report Id: GFL222 [WCAMIS] 02605191 (Generated: 12/28/2023 09:28:46) Rev: 1

CALA

ISO 17025:2017 Accredited Laboratory

> T: (519)940-4167 F: Submitted By: Kim Thompson