


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
Framo [450228580]
Machine Id
HPU VRC Hyd. Power (S/N Sample Tag IH-65201-S1)
Component
Hydraulic System
Fluid
PETRO CANADA HYDREX MV ARCTIC 15 (310 LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	PC0078224	PC0076635	PC0062109
Sample Date	Client Info	24 Nov 2023	26 Oct 2023	04 Oct 2023
Machine Age	hrs	Client Info	0	0
Oil Age	hrs	Client Info	0	0
Oil Changed	Client Info	N/A	N/A	N/A
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2	
Water	WC Method	>0.05	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
PQ	ASTM D8184*	0	0	0
Iron	ppm	ASTM D5185(m) >20	0	0
Chromium	ppm	ASTM D5185(m) >10	0	0
Nickel	ppm	ASTM D5185(m) >10	<1	<1
Titanium	ppm	ASTM D5185(m)	0	0
Silver	ppm	ASTM D5185(m)	0	<1
Aluminum	ppm	ASTM D5185(m) >10	<1	0
Lead	ppm	ASTM D5185(m) >20	<1	<1
Copper	ppm	ASTM D5185(m) >20	<1	<1
Tin	ppm	ASTM D5185(m) >10	0	0
Antimony	ppm	ASTM D5185(m)	0	0
Vanadium	ppm	ASTM D5185(m)	0	0
Beryllium	ppm	ASTM D5185(m)	0	0
Cadmium	ppm	ASTM D5185(m)	0	0






ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m) 0	0	0
Barium	ppm	ASTM D5185(m) 0	0	<1
Molybdenum	ppm	ASTM D5185(m) 0	0	0
Manganese	ppm	ASTM D5185(m) 0	0	0
Magnesium	ppm	ASTM D5185(m) 0	<1	0
Calcium	ppm	ASTM D5185(m) 50	28	30
Phosphorus	ppm	ASTM D5185(m) 330	322	322
Zinc	ppm	ASTM D5185(m) 430	389	394
Sulfur	ppm	ASTM D5185(m) 760	777	755
Lithium	ppm	ASTM D5185(m)	<1	<1

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >15	<1	0
Sodium	ppm	ASTM D5185(m)	0	0
Potassium	ppm	ASTM D5185(m) >20	0	0

OIL ANALYSIS REPORT



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PC0078224 **Received** : 28 Dec 2023
Lab Number : **02605543** **Diagnosed** : 02 Jan 2024
Unique Number : 5698628 **Diagnostician** : Kevin Marson
Test Package : MAR 2 (Additional Tests: KV100, PQ, VI)

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

FLUID CLEANLINESS		method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647			637	659	545
Particles >6µm	ASTM D7647	>640		155	155	141
Particles >14µm	ASTM D7647	>40		9	14	16
Particles >21µm	ASTM D7647	>10		2	4	5
Particles >38µm	ASTM D7647	>3		0	2	1
Particles >71µm	ASTM D7647	>3		0	1	0
Oil Cleanliness	ISO 4406 (c)	>--/16/12		16/14/10	17/14/11	16/14/11

FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.70	0.48	0.49	0.64

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.05	NEG	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG	NEG

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	13.6	12.9	13.0	13.1
Visc @ 100°C	cSt	ASTM D7279(m)	5.23	4.8	4.8	4.8
Viscosity Index (VI)	Scale	ASTM D2270*	394	364	359	355

SAMPLE IMAGES		method	limit/base	current	history1	history2
Color						
Bottom						