


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**TEAM 3**  
Machine Id  
**166191**

Component  
**Hydraulic System**  
Fluid

**PETRO CANADA HYDREX AW 46 (50 LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>PC0076948</b>	PC0069855	PC0074795
Sample Date	Client Info	<b>14 Jan 2024</b>	20 Oct 2023	08 Aug 2023
Machine Age	mths	Client Info	<b>0</b>	0
Oil Age	mths	Client Info	<b>0</b>	0
Oil Changed	Client Info	<b>N/A</b>	N/A	N/A
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.05	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185(m) >20	<b>&lt;1</b>	<1	1
Chromium	ppm ASTM D5185(m) >20	<b>0</b>	0	0
Nickel	ppm ASTM D5185(m) >20	<b>&lt;1</b>	0	0
Titanium	ppm ASTM D5185(m)	<b>0</b>	0	0
Silver	ppm ASTM D5185(m)	<b>0</b>	<1	0
Aluminum	ppm ASTM D5185(m) >20	<b>&lt;1</b>	0	<1
Lead	ppm ASTM D5185(m) >20	<b>0</b>	0	0
Copper	ppm ASTM D5185(m) >20	<b>&lt;1</b>	<1	<1
Tin	ppm ASTM D5185(m) >20	<b>0</b>	0	0
Antimony	ppm ASTM D5185(m)	<b>0</b>	0	0
Vanadium	ppm ASTM D5185(m)	<b>0</b>	0	0
Beryllium	ppm ASTM D5185(m)	<b>0</b>	0	0
Cadmium	ppm ASTM D5185(m)	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185(m) 0	<b>0</b>	<1	0
Barium	ppm ASTM D5185(m) 0	<b>0</b>	<1	0
Molybdenum	ppm ASTM D5185(m) 0	<b>0</b>	0	0
Manganese	ppm ASTM D5185(m) 0	<b>0</b>	0	0
Magnesium	ppm ASTM D5185(m) 0	<b>&lt;1</b>	0	<1
Calcium	ppm ASTM D5185(m) 50	<b>49</b>	48	48
Phosphorus	ppm ASTM D5185(m) 330	<b>330</b>	320	349
Zinc	ppm ASTM D5185(m) 430	<b>402</b>	413	417
Sulfur	ppm ASTM D5185(m) 760	<b>796</b>	731	768
Lithium	ppm ASTM D5185(m)	<b>&lt;1</b>	<1	<1






## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185(m) >15	<b>0</b>	0	0
Sodium	ppm ASTM D5185(m)	<b>&lt;1</b>	<1	<1
Potassium	ppm ASTM D5185(m) >20	<b>&lt;1</b>	0	<1

## FLUID CLEANLINESS

method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647	<b>1382</b>	1246	---
Particles >6µm	ASTM D7647 >1300	<b>363</b>	482	---
Particles >14µm	ASTM D7647 >160	<b>29</b>	31	---
Particles >21µm	ASTM D7647 >40	<b>11</b>	7	---
Particles >38µm	ASTM D7647 >10	<b>2</b>	1	---
Particles >71µm	ASTM D7647 >3	<b>0</b>	1	---
Oil Cleanliness	ISO 4406 (c) >--/17/14	<b>18/16/12</b>	17/16/12	---

# OIL ANALYSIS REPORT




FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.70	<b>0.42</b>	0.42	---

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Precipitate	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Silt	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	Visual*	NONE	<b>NONE</b>	NONE	VLITE
Sand/Dirt	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	Visual*	>0.05	<b>NEG</b>	NEG	NEG
Free Water	scalar	Visual*		<b>NEG</b>	NEG	NEG

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46.4	<b>45.6</b>	45.7	45.5
Visc @ 100°C	cSt	ASTM D7279(m)	6.92	<b>7.2</b>	7.2	7.2
Viscosity Index (VI)	Scale	ASTM D2270*	104	<b>118</b>	117	118

## SAMPLE IMAGES



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : PC0076948 **Received** : 24 Jan 2024  
**Lab Number** : **02610880** **Diagnosed** : 25 Jan 2024  
**Unique Number** : 5719975 **Diagnostician** : Wes Davis  
**Test Package** : IND 2 ( Additional Tests: KV100, VI )

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.

**Dryden Fibre**  
 Box 3001, 1 Duke Street  
 Dryden, ON  
 CA P8N 2Z7  
 Contact: Adebukola Adekanye  
 aadekanye@drydenfibre.ca  
 T: (807)223-9950  
 F: (807)223-9176