




OIL ANALYSIS REPORT

Sample Rating Trend



ISO



Machine Id
9254
Component
Hydraulic System
Fluid
PETRO CANADA HYDREX MV 32 (--- GAL)

DIAGNOSIS

Recommendation

Nous vous recommandons de vérifier tous les endroits par lesquels des contaminants peuvent pénétrer dans le système. Nous vous recommandons de remplacer le filtre et d'utiliser un système de filtrage hors-ligne afin d'améliorer la propreté du fluide. Le reniflard d'air doit être réparé. S'il n'est pas classé, nous vous recommandons de le remplacer par un reniflard à air adapté au micron et / ou au dessicant. Si évalué, nous vous recommandons de réparer / remplacer le reniflard. Échantillonner de nouveau dans 30 à 45 jours afin de contrôler la situation.

Wear

Les taux d'usure de tous les composants sont normaux.

Contamination

Il y a une quantité élevée de matières particulaires (2 à 100 µm de taille) présente dans l'huile.

Fluid Condition

L'huile peut encore servir si la contamination peut être réduite à un niveau acceptable.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0107590	GFL0055344	GFL0043173
Sample Date	Client Info	01 Feb 2024	04 Oct 2022	11 Apr 2022
Machine Age	kms	462259	17602	16706
Oil Age	kms	0	0	0
Oil Changed	Client Info	N/A	N/A	Not Changd
Sample Status		SEVERE	SEVERE	SEVERE

CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.1	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185(m) >50	4	1	14
Chromium	ppm ASTM D5185(m) >10	<1	0	<1
Nickel	ppm ASTM D5185(m) >4	0	0	<1
Titanium	ppm ASTM D5185(m)	0	0	0
Silver	ppm ASTM D5185(m)	0	0	0
Aluminum	ppm ASTM D5185(m) >5	<1	<1	2
Lead	ppm ASTM D5185(m) >4	0	0	<1
Copper	ppm ASTM D5185(m) >15	<1	<1	<1
Tin	ppm ASTM D5185(m) >4	0	0	0
Antimony	ppm ASTM D5185(m)	0	0	0
Vanadium	ppm ASTM D5185(m)	0	0	0
Beryllium	ppm ASTM D5185(m)	0	0	0
Cadmium	ppm ASTM D5185(m)	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185(m) 0	0	<1	1
Barium	ppm ASTM D5185(m) 0	0	0	0
Molybdenum	ppm ASTM D5185(m) 0	0	0	<1
Manganese	ppm ASTM D5185(m) 1	0	0	<1
Magnesium	ppm ASTM D5185(m) 0	5	<1	6
Calcium	ppm ASTM D5185(m) 50	61	42	77
Phosphorus	ppm ASTM D5185(m) 330	346	370	360
Zinc	ppm ASTM D5185(m) 430	426	426	437
Sulfur	ppm ASTM D5185(m) 760	828	865	877
Lithium	ppm ASTM D5185(m)	<1	<1	<1

CONTAMINANTS




method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185(m) >15	1	<1	4
Sodium	ppm ASTM D5185(m)	1	<1	5
Potassium	ppm ASTM D5185(m) >20	1	0	3

FLUID CLEANLINESS

method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647 >5000	145603	55747	151079
Particles >6µm	ASTM D7647 >1300	44617	14687	38522
Particles >14µm	ASTM D7647 >160	432	1425	136
Particles >21µm	ASTM D7647 >40	96	396	22
Particles >38µm	ASTM D7647 >10	6	12	0
Particles >71µm	ASTM D7647 >3	0	1	0
Oil Cleanliness	ISO 4406 (c) >19/17/14	24/23/16	23/21/18	24/22/14




OIL ANALYSIS REPORT







VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	VLITE	VLITE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	31.9	32.0	32.3

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **GFL Environmental - 747 - GMA - Solid Waste**
Sample No. : GFL0107590 **Received** : 05 Feb 2024 4 Chemin du Tremblay,
Lab Number : 02613446 **Tested** : 06 Feb 2024 Boucherville, QC
Unique Number : 5722541 **Diagnosed** : 06 Feb 2024 - Wes Davis CA J4B 6Z5
Test Package : MOB 1 (Additional Tests: PrtCount) Contact: Steve Voyer
svoyer@matrec.ca

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.