




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
831048
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON GEO LD 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0099619	GFL0091627	GFL0070720
Sample Date	Client Info		29 Jan 2024	21 Sep 2023	22 Feb 2023
Machine Age	kms	Client Info	53225	3003	1901
Oil Age	kms	Client Info	0	0	852
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>120	17	31	28
Chromium	ppm	ASTM D5185(m)	>20	<1	4	2
Nickel	ppm	ASTM D5185(m)	>5	<1	1	1
Titanium	ppm	ASTM D5185(m)	>2	0	0	<1
Silver	ppm	ASTM D5185(m)	>2	0	<1	0
Aluminum	ppm	ASTM D5185(m)	>20	2	4	3
Lead	ppm	ASTM D5185(m)	>40	<1	3	2
Copper	ppm	ASTM D5185(m)	>330	1	3	4
Tin	ppm	ASTM D5185(m)	>15	<1	1	1
Antimony	ppm	ASTM D5185(m)		0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0

ADDITIVES

	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)	50	12	6	7
Barium	ppm	ASTM D5185(m)	5	0	<1	0
Molybdenum	ppm	ASTM D5185(m)	50	52	66	59
Manganese	ppm	ASTM D5185(m)	0	0	<1	2
Magnesium	ppm	ASTM D5185(m)	560	549	701	647
Calcium	ppm	ASTM D5185(m)	1510	1615	1913	1810
Phosphorus	ppm	ASTM D5185(m)	780	704	853	844
Zinc	ppm	ASTM D5185(m)	870	896	1084	996
Sulfur	ppm	ASTM D5185(m)	2040	2067	2111	2108
Lithium	ppm	ASTM D5185(m)		<1	<1	<1

CONTAMINANTS



	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>25	4	9	9
Sodium	ppm	ASTM D5185(m)		7	13	11
Potassium	ppm	ASTM D5185(m)	>20	2	4	<1

INFRA-RED

	method	limit/base	current	history1	history2	
Soot %	%	ASTM D7844*	>4	0	0	0
Nitration	Abs/cm	ASTM D7624*	>20	11.0	12.9	5.8
Sulfation	Abs.1mm	ASTM D7415*	>30	21.4	30.3	17.3



OIL ANALYSIS REPORT











FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs./1mm	ASTM D7414*	>25	18.2	26.9	9.3
Base Number (BN)	mg KOH/g	ASTM D2896*	10.2	7.71	5.33	4.53

VISUAL		method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG	NEG

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	15.1	14.8	14.6	14.5

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0099619
Lab Number : 02614201
Unique Number : 5723296
Test Package : MOB 2
Received : 08 Feb 2024
Tested : 12 Feb 2024
Diagnosed : 12 Feb 2024 - Wes Davis

GFL Environmental - 550 - Rocky View County
 220 Carmek Blvd
 Rocky View County, AB
 CA T1X 1X1
 Contact: GFL Calgary
 calgarymaintenance@gflenv.com
 T: (403)369-6163

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.