

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area CAPLAN Machine Id 8322

Component Front Center Transmission (Auto) Fluid PETRO CANADA DURADRIVE HD SYNTHETIC ATF (20 LTR)

SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0091119		
Sample Date		Client Info		09 Feb 2024		
Machine Age	hrs	Client Info		16560		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>160	54		
Chromium	ppm	ASTM D5185(m)	>5	0		
Nickel	ppm	ASTM D5185(m)	>5	<1		
Titanium	ppm	ASTM D5185(m)		<1		
Silver	ppm	ASTM D5185(m)	>5	0		
Aluminum	ppm	ASTM D5185(m)	>50	8		
Lead	ppm	ASTM D5185(m)	>50	2		
Copper	ppm	ASTM D5185(m)	>225	6		
Tin	ppm	ASTM D5185(m)	>10	<1		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		35		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		<1		
Magnesium	ppm	ASTM D5185(m)		2		
Calcium	ppm	ASTM D5185(m)		97		
Phosphorus	ppm	ASTM D5185(m)		195		
Zinc	ppm	ASTM D5185(m)		5		
Sulfur	ppm	ASTM D5185(m)		1256		
Lithium	ppm	ASTM D5185(m)		1		
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>20	10		
Sodium	ppm	ASTM D5185(m)		106		
Potassium	ppm	ASTM D5185(m)	>20	1		
Glycol	%	ASTM D7922*		0.0		

Recommendation

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

Wear

Les taux d'usure de tous les composants sont normaux.

Contamination

Il n'y a aucun indice de contamination dans le fluide.


Fluid Condition


L'état de le fluide est acceptable pour la durée de service.




OIL ANALYSIS REPORT

VISUAL





r ^{0.25}	VISUAL		methoa	iimii/base	current	riistory i	nistoryz
0.20	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
-0.15 % giycol	Precipitate	scalar	Visual*	NONE	NONE		
0.10 单	Silt	scalar	Visual*	NONE	NONE		
05	Debris	scalar	Visual*	NONE	NONE		
0	Sand/Dirt	scalar	Visual*	NONE	NONE		
	Appearance	scalar	Visual*	NORML	NORML		
	Odor	scalar	Visual*	NORML	NORML		
	Emulsified Water	scalar	Visual*	>0.1	NEG		
	Free Water	scalar	Visual*		NEG		
	FLUID PROPI	ERTIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)	36.1	30.2		
	SAMPLE IMA	GES	method	limit/base	current	history1	history2
Feb9/24	Color					no image	no image
	Bottom					no image	no image
	GRAPHS						
	Iron (ppm)				Lead (ppm)		
	300 T Severe			150	T		
	E 200 Abnormal			E 100	Severe Abnormal		
	100			50			
	Feb 9/24			Feb9/24	Feb 9/24		
	Feb			Feb	Feb		
	Aluminum (ppm)				Chromium (pj	pm)	
	100 Severe			15	Sminn		
	Abnormal			E ¹⁰	Abnormal		
	0			5			
	Feb9/24			Feb9/24	Feb 9/24 -		
	Feb			Feb	Feb		
	Copper (ppm)				Silicon (ppm)		
	600 400 Severe			40	Severe		
	Abnormal			톱 20	Abnormal		
	0			0			
	Feb 9/24			Feb 9/24	Feb9/24		
	∽ Viscosity @ 40°C			Ľ	⊥ Additives		
	50 T			300	I.		
	(20 40 - Abnormal 영화동 정 30 - Abnormal			툴 ²⁰⁰ 100	calcium	S	
	경 30 P				ZINC		
	**			Feb9/24	9/24		
	Feb 3/2 [,]			Feb.	Feb9/24		
	: WearCheck - C8-117 : GFL0091119 : 02615708 : 5724803 : MOB 1 (Additional T	Rece Teste Diagr	ived : 14 ed : 15 nosed : 16	igton, ON L7L 4 Feb 2024 5 Feb 2024 Feb 2024 - Kev			791 - Rimous e de L`Industr Rimouski, C CA G5M 1W



Contact: Vincent Maltais info@foretsstar.com T: 4(18)388-2626 F: (418)388-2038



CALA

ISO 17025:2017