

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area CAPLAN Machine Id 8322

Component Rear Front Differential

PETRO CANADA TRAXON SYNTHETIC 75W90 (15 LTR)

SAMPLE INFORMATION method GFL0091117 Sample Number **Client Info** 09 Feb 2024 Sample Date Client Info 16560 Machine Age hrs **Client Info** Oil Age hrs Client Info 0 Oil Changed **Client Info** Oil Added NORMAL Sample Status CONTAMINATION Water WC Method >.2 NEG WEAR METALS ASTM D5185(m) >500 151 Iron ppm Chromium ASTM D5185(m) >10 1 ppm Nickel ppm ASTM D5185(m) >10 <1 Titanium ASTM D5185(m) 0 ppm Silver 0 ppm ASTM D5185(m) Aluminum ppm ASTM D5185(m) >25 6 Lead ASTM D5185(m) >25 <1 ppm >100 <1 Copper ppm ASTM D5185(m) Tin ASTM D5185(m) >10 0 ppm Antimony 0 ppm ASTM D5185(m) >5 Vanadium 0 ppm ASTM D5185(m) Beryllium ppm ASTM D5185(m) 0 Cadmium 0 ASTM D5185(m) ppm ADDITIVES Boron ppm ASTM D5185(m) 328 238 Barium ASTM D5185(m) <1 ppm 1 0 Molybdenum ASTM D5185(m) ppm Manganese ASTM D5185(m) 2 ppm Magnesium ASTM D5185(m) 1 3 ppm 20 Calcium ppm ASTM D5185(m) 7 Phosphorus ppm ASTM D5185(m) 1145 1408 ASTM D5185(m) 3 Zinc ppm 5 Sulfur ASTM D5185(m) 17909 23733 ppm Lithium ppm ASTM D5185(m) <1 CONTAMINANTS Silicon ASTM D5185(m) >75 36 ppm Sodium ppm ASTM D5185(m) 9 3 Potassium ppm ASTM D5185(m) >20

Recommendation

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition. (Customer Sample Comment: Top Up Amount: 2,5 LTR)

Fluic

Wear

Les taux d'usure de tous les composants sont normaux.

Contamination

Il n'y a aucun indice de contamination dans l'huile.

Fluid Condition

L'état de l'huile est acceptable pour la durée de service.



OIL ANALYSIS REPORT

140 Abno	rmal	 	 	 	 	 	 	
130								
120								
110 Base								
Base								
3 100		 		 	 	 	 	_
90 -								
80 - Abno	rmal							
00-0								
70								

	White Metal Yellow Metal	scalar	Visual*				
	Yellow Metal		visuai	NONE	NONE		
		scalar	Visual*	NONE	NONE		
	Precipitate		Visual*	NONE	NONE		
	Silt		Visual*	NONE	VLITE		
	Debris	scalar	Visual*	NONE	NONE		
	Sand/Dirt		Visual*	NONE	NONE		
Feb 9/24	Appearance	scalar	Visual*	NORML	NORML		
Feb	Odor	scalar	Visual*	NORML	NORML		
	Emulsified Water	scalar	Visual*	>.2	NEG		
	Free Water		Visual*		NEG		
	FLUID PROPE	RTIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)	99.6	96.6		
	SAMPLE IMAG	ES	method	limit/base	current	history1	history2
	Color					no image	no image
	Bottom					no image	no image
	GRAPHS						
	Iron (ppm)				Lead (ppm)		
	2000 Severe			150	Savara		
uda	1000 - Abnormal			E 100			
	0			0	0		
	Feb 9/2 4			Feb 9/24	Feb9/24		
	Aluminum (ppm)				Chromium (pp	om)	
	150			30	Severe		
	E 100 Severe			²⁰	Abnormal		
	Abrionna				1		
	24 10			24			
	Feb 9/24			Feb 9/24	Feb 9/24		
	Copper (ppm)				Silicon (ppm)		
	300 T			300			
1	200 Abnormal			²⁰⁰ 100	- Gevere		
					-		
	24			24			
	Feb 9/24			Feb 9/24	Feb 9/2 4		
	Viscosity @ 40°C			1500	Additives		
100	200 Abnormal			- 1000	(
007	Abnormal Base			E 1000	- zinc		
1	04					2	
	Feb 9/24			Feb 9/24	Feb 9/24		
nple No. Number ue Number t Package		Receiv Testeo Diagno ice at 1-80	ved : 14 d : 14 osed : 15 00-268-213	4 Feb 2024 4 Feb 2024 5 Feb 2024 - Kev	in Marson	350 Avenue Contact: info@	791 - Rimous e de L`Industr Rimouski, Q CA G5M 1W Vincent Malta oforetsstar.co 4(18)388-262

To discuss this sample Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Submitted By: Vincent Maltais

Page 2 of 2

F: (418)388-2038

CALA

ISO 17025:2017 Accredited Laboratory