

[450267885] MC-04201-S1

OIL ANALYSIS REPORT

Sample Rating Trend







Component **Unknown Component** {not provided} (--- GAL)

DIAGNOSIS

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample. Please provide more complete information on your next sample.

Wear


All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the sample is suitable for further service.




		method				history2
Sample Number		Client Info		PC		
Sample Date		Client Info		21 Feb 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATI	ON	method	limit/base	current	history1	history2
Water		WC Method		NEG		
WEAR METALS	S	method	limit/base	current	history1	history2
PQ		ASTM D8184*		0		
Iron	ppm	ASTM D5185(m)		0		
Chromium	ppm	ASTM D5185(m)		0		
Nickel	ppm	ASTM D5185(m)		<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		<1		
Lead	ppm	ASTM D5185(m)		<1		
Copper	ppm	ASTM D5185(m)		<1		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		0		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		<1		
Calcium	ppm	ASTM D5185(m)		<1		
Phosphorus	ppm	ASTM D5185(m)		347		
Zinc	ppm	ASTM D5185(m)		51		
Sulfur	ppm	ASTM D5185(m)		1154		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		0		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	1		



OIL ANALYSIS REPORT

	icle Cou	int			20
491,520					26
pevere					22 8
7,680 Abnorm 1,920 - 480 - 120 - 30 - 8 -	al				
1,920		1 may 1			-20 Cleanliness Code -18 999 Cleanliness Code -14 -12 sc Code -10 -10
480 -	1.				-16 0
120-					-14
30-		1			-12 8
		-			
2 -					-8
0. 4µ	6µ	14µ	21µ	38 ^j µ	71µ
Acid	Numbe	er			
0.12					
(D)H00 0.06 Will be a constrained with the second s					
Bull					
-0.00					
≥ 0.04					
₽ 0.02					
0.00					
Feb21/24					Feb21/24
Feb2					Feb2
PQ					
250					
200 Severe	2				
150					
150 문					
100 Abnor	mal				
50-					
50-					
04					4
Feb21/24					Feb21/24
Feb					Feb
Part	icle Trei	nd			
^{6k} T					
= 5k - Stonio	mar 4μm 6μm				



	INESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	3712		
Particles >6µm		ASTM D7647	>1300	750		
Particles >14µm		ASTM D7647	>160	17		
Particles >21µm		ASTM D7647	>40	2		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	1		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	19/17/11		
FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.10		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt		Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor		Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*		NEG		
Free Water		Visual*		NEG		
FLUID PROPER	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)		39.0		
Visc @ 100°C	cSt	ASTM D7279(m)		6.6		
Viscosity Index (VI)	Scale	ASTM D2270*		123		
SAMPLE IMAG	ES	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
PrtFilter					no image	no image

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Suncor - Terra Nova Projects : PC Received : 12 Mar 2024 Scotia Centre, 235 Water Strret Lab Number : 02621422 Tested : 14 Mar 2024 St. John`s, NL ISO 17025:2017 Accredited Laboratory Unique Number : 5746541 Diagnosed : 14 Mar 2024 - Kevin Marson CA A1C 1B6 Test Package : MAR 2 (Additional Tests: BottomAnalysis, FILTERPATCH, KV100, PQ, PRTCOUNT, PrtFilter, Wontact: Josh Hynes To discuss this sample report, contact Customer Service at 1-800-268-2131. joshynes@suncor.com Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. T: (709)778-3575 Validity of results and interpretation are based on the sample and information as supplied. F: (709)724-2835