




OIL ANALYSIS REPORT

Sample Rating Trend

ISO



Machine Id
711013
 Component
Hydraulic System
 Fluid
PETRO CANADA HYDREX MV 32 (--- GAL)



DIAGNOSIS

Recommendation

Vérifier les scelles et/ou les filtres pour des points d'entrée des contaminants. Le reniflard d'air doit être réparé. S'il n'est pas classé, nous vous recommandons de le remplacer par un reniflard à air adapté au micron et / ou au dessicant. Si évalué, nous vous recommandons de réparer / remplacer le reniflard. Nous avons pris note que le filtre a été remplacé au moment de l'échantillonnage. Échantillonner de nouveau dans 30 à 45 jours afin de contrôler la situation.

Wear

Les taux d'usure de tous les composants sont normaux.

Contamination

Il y a une grande quantité de limon (particules de 4 à 14 microns) dans l'huile.

Fluid Condition

L'huile peut encore servir si la contamination peut être réduite à un niveau acceptable.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0096386	GFL0073363	GFL0062052
Sample Date	Client Info		01 Mar 2024	03 Apr 2023	10 Oct 2022
Machine Age	kms	Client Info	121190	4337	3205
Oil Age	kms	Client Info	0	1200	3205
Oil Changed	Client Info		Not Chngd	Not Chngd	N/A
Sample Status			SEVERE	SEVERE	SEVERE

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m) >50	9	9	9
Chromium	ppm	ASTM D5185(m) >10	1	<1	<1
Nickel	ppm	ASTM D5185(m) >4	<1	0	0
Titanium	ppm	ASTM D5185(m)	0	<1	<1
Silver	ppm	ASTM D5185(m)	0	0	0
Aluminum	ppm	ASTM D5185(m) >5	2	1	1
Lead	ppm	ASTM D5185(m) >4	<1	<1	0
Copper	ppm	ASTM D5185(m) >15	<1	<1	1
Tin	ppm	ASTM D5185(m) >4	0	0	0
Antimony	ppm	ASTM D5185(m)	0	0	0
Vanadium	ppm	ASTM D5185(m)	0	0	0
Beryllium	ppm	ASTM D5185(m)	0	0	0
Cadmium	ppm	ASTM D5185(m)	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m) 0	<1	<1	2
Barium	ppm	ASTM D5185(m) 0	0	0	0
Molybdenum	ppm	ASTM D5185(m) 0	<1	3	<1
Manganese	ppm	ASTM D5185(m) 1	0	0	0
Magnesium	ppm	ASTM D5185(m) 0	24	51	15
Calcium	ppm	ASTM D5185(m) 50	94	113	75
Phosphorus	ppm	ASTM D5185(m) 330	369	393	353
Zinc	ppm	ASTM D5185(m) 430	454	440	405
Sulfur	ppm	ASTM D5185(m) 760	892	875	786
Lithium	ppm	ASTM D5185(m)	<1	<1	<1

CONTAMINANTS




	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >15	4	4	3
Sodium	ppm	ASTM D5185(m)	11	12	10
Potassium	ppm	ASTM D5185(m) >20	2	<1	<1

FLUID CLEANLINESS

	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647	>5000	▲ 87923	▲ 50779	▲ 59379
Particles >6µm	ASTM D7647	>1300	▲ 12690	▲ 6777	▲ 9778
Particles >14µm	ASTM D7647	>160	84	▲ 383	▲ 621
Particles >21µm	ASTM D7647	>40	18	● 71	▲ 178
Particles >38µm	ASTM D7647	>10	2	1	7
Particles >71µm	ASTM D7647	>3	1	0	1
Oil Cleanliness	ISO 4406 (c)	>19/17/14	▲ 24/21/14	▲ 23/20/16	▲ 23/20/16




OIL ANALYSIS REPORT







VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 40°C	cSt	ASTM D7279(m)	31.9	32.5	33.0	32.0

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **GFL Environmental - 747 - GMA - Solid Waste**
Sample No. : GFL0096386 **Received** : 19 Mar 2024 4 Chemin du Tremblay,
Lab Number : 02623087 **Tested** : 20 Mar 2024 Boucherville, QC
Unique Number : 5748206 **Diagnosed** : 20 Mar 2024 - Wes Davis CA J4B 6Z5
Test Package : MOB 1 (Additional Tests: PrtCount) Contact: Steve Voyer
svoyer@matrec.ca

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.